

**norm****NEN-EN 12976-2**

Thermische zonne-energiesystemen en componenten - Fabrieksmatig geproduceerde systemen - Deel 2: Beproevingsmethoden

Publicatie uitsluitend voor commentaar

Thermal solar systems and components - Factory made systems - Part 2: test methods

juni 2014  
ICS 27.160

Commentaar vóór 2014-09-15

Vervangt NEN-EN 12976-2:2012 Ontw. Zal vervangen NEN-EN 12976-2:2006

Als Europees normontwerp is gepubliceerd: prEN 12976-2:2014, IDT

Definitief vastgestelde normen zullen als Nederlandse norm gelden. Daarom wordt dit normontwerp in Nederland voor commentaar gepubliceerd. Op het ontwerp ingebracht commentaar zal aan de bevoegde normcommissie worden voorgelegd die hiermee rekening zal houden bij de bepaling van de Nederlandse stem. Indien er geen bezwaar bij NEN wordt gebracht, kan dat leiden tot ongewijzigde definitieve vaststelling van het ontwerp als norm.

Van Europese normen bestaan drie officiële versies: Engels, Frans en Duits. Voor Nederland zal de Engelse versie gelden. Daarnaast kan er gekozen worden voor een andere geautoriseerde versie in het Nederlands.

Normcommissie 349010 "Zonnewarmte"



**THIS PUBLICATION IS COPYRIGHT PROTECTED**

**DEZE PUBLICATIE IS AUTEURSRECHTELIJK BESCHERMD**

Apart from exceptions provided by the law, nothing from this publication may be duplicated and/or published by means of photocopy, microfilm, storage in computer files or otherwise, which also applies to full or partial processing, without the written consent of the Netherlands Standardization Institute.

The Netherlands Standardization Institute shall, with the exclusion of any other beneficiary, collect payments owed by third parties for duplication and/or act in and out of law, where this authority is not transferred or falls by right to the Reproduction Rights Foundation.

Auteursrecht voorbehouden. Behoudens uitzondering door de wet gesteld mag zonder schriftelijke toestemming van het Nederlands Normalisatie-instituut niets uit deze uitgave worden verveelvoudigd en/of openbaar gemaakt door middel van fotokopie, microfilm, opslag in computerbestanden of anderszins, hetgeen ook van toepassing is op gehele of gedeeltelijke bewerking.

Het Nederlands Normalisatie-instituut is met uitsluiting van ieder ander gerechtigd de door derden verschuldigde vergoedingen voor verveelvoudiging te innen en/of daartoe in en buiten rechte op te treden, voor zover deze bevoegdheid niet is overgedragen c.q. rechtens toekomt aan de Stichting Reprorecht.

Although the utmost care has been taken with this publication, errors and omissions cannot be entirely excluded. The Netherlands Standardization Institute and/or the members of the committees therefore accept no liability, not even for direct or indirect damage, occurring due to or in relation with the application of publications issued by the Netherlands Standardization Institute.

Hoewel bij deze uitgave de uiterste zorg is nagestreefd, kunnen fouten en onvolledigheden niet geheel worden uitgesloten. Het Nederlands Normalisatie-instituut en/of de leden van de commissies aanvaarden derhalve geen enkele aansprakelijkheid, ook niet voor directe of indirecte schade, ontstaan door of verband houdend met toepassing van door het Nederlands Normalisatie-instituut gepubliceerde uitgaven.

Voorbeeld  
Preview

May 2014

ICS 27.160

Will supersede EN 12976-2:2006

English Version

## Thermal solar systems and components - Factory made systems - Part 2: test methods

Installations solaires thermiques et leurs composants -  
Installations préfabriquées en usine - Partie 2: Méthodes  
d'essai

Thermische Solaranlagen und ihre Bauteile - Vorgefertigte  
Anlagen - Teil 2: Prüfverfahren

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 312.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

**Warning** : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels**

## Contents

Page

Foreword.....	3
Introduction.....	4
1 Scope.....	6
2 Normative references.....	6
3 Terms and definitions.....	6
4 Symbols and abbreviations.....	7
5 Testing.....	7
5.1 Freeze resistance.....	7
5.2 Over temperature protection.....	9
5.3 Pressure resistance.....	10
5.4 Water contamination.....	12
5.5 (New) Testing the resistance against mechanical load.....	13
5.6 Lightning protection.....	17
5.7 Safety equipment.....	17
5.8 Labelling.....	18
5.9 Thermal performance characterization.....	18
5.10 Ability of solar-plus-supplementary systems to cover the load.....	23
5.11 Reverse flow protection.....	25
5.12 Electrical safety.....	25
Annex A (normative) Thermal performance presentation sheet.....	26
Annex B (normative) Reference conditions for performance prediction.....	29
B.1 General.....	29
B.2 Pipe diameter and insulation thickness.....	31
B.3 Calculation of cold water temperature at reference location.....	32
Annex C (informative) Assessment of the ability of solar DWH systems to resist the extreme climatic conditions”.....	34
C.1 Indoor and outdoor test procedure for assessment of the frost resistance of solar DWH systems with outdoor storage tank or system using heat transfer fluid with the risk of freezing.....	34
C.2 Indoor test procedure for assessment of the reliability of solar DWH systems in respect of overheating protection.....	37
Annex D (informative) Ageing test for thermostatic valves.....	42
D.1 General.....	42
D.2 Test arrangement.....	42
D.3 Test Procedure.....	43
D.4 Results.....	43
Annex E (informative) Lightning protection test for solar heating systems.....	44
E.1 Field of application.....	44
E.2 Purpose.....	44
E.3 Requirements.....	44
E.4 Apparatus.....	45
E.5 Test procedure.....	45
E.6 Report.....	46
E.7 Conclusions.....	46
Annex F (informative) Lightning Protection testing sheet.....	47
Bibliography.....	51

## Foreword

This European Standard (EN 12976-2:2014) has been prepared by Technical Committee CEN/TC 312 "Thermal solar systems and components", the secretariat of which is held by ELOT.

This European Standard will supersede EN 12976-2:2006.

Forbiede  
Preview

## Introduction

### Drinking water quality

In respect of potential adverse effects on the quality of water intended for human consumption, caused by the product covered by this standard:

- a) This standard provides no information as to whether the product may be used without restriction in any of the Member States of the EU or EFTA;
- b) It should be noted that, while awaiting the adoption of verifiable European criteria, existing national regulations concerning the use and/or the characteristics of this product remain in force.

### Factory Made and Custom Built solar heating systems

The standards EN 12976-1, EN 12976-2, EN 12977-1:2012, EN 12977-2:2012, EN 12977-3, EN 12977-4:2012 and EN 12977-5:2012 distinguish two categories of solar heating systems: **Factory Made** solar heating systems and **Custom Built** solar heating systems. The classification of a system as Factory Made or Custom Built is a choice of the final supplier, in accordance with the following definitions:

**Factory Made solar heating systems** are batch products with one trade name, sold as complete and ready to install kits, with fixed configurations. Systems of this category are considered as a single product and assessed as a whole.

If a Factory Made Solar Heating System is modified by changing its configuration or by changing one or more of its components, the modified system is considered as a new system for which a new test report is necessary. Requirements and test methods for Factory Made solar heating systems are given in EN 12976-1 and EN 12976-2.

**Custom Built solar heating systems** are either uniquely built, or assembled by choosing from an assortment of components. Systems of this category are regarded as a set of components. The components are separately tested and test results are integrated to an assessment of the whole system. Requirements for Custom Built solar heating systems are given in EN 12977-1:2012; test methods are specified in EN 12977-2:2012, EN 12977-3, EN 12977-4:2012 and EN 12977-5:2012.

Custom Built solar heating systems are subdivided into two categories:

- **Large Custom Built systems** are uniquely designed for a specific situation. In general HVAC engineers, manufacturers or other experts design them.
- **Small Custom Built systems** offered by a company are described in a so-called assortment file, in which all components and possible system configurations, marketed by the company, are specified. Each possible combination of a system configuration with components from the assortment is considered as **one** Custom Built system.

Table 1 shows the division for different system types:

**Table 1 - Division for factory made and custom built solar heating systems**

Factory Made Solar Heating Systems (EN 12976-1:2006 and EN 12976-2:2006)	Custom Built Solar Heating Systems (EN 12977-1:2012, EN 12977-2:2012 and EN 12977-3)
Integral collector storage systems for domestic hot water preparation	Forced-circulation systems for hot water preparation and/or space heating, assembled using components
Thermosiphon systems for domestic hot water preparation	and configurations described in an assortment file (mostly small systems)
Forced-circulation systems as batch product with fixed configuration for domestic hot water preparation	Uniquely designed and assembled systems for hot water preparation and/or space heating (mostly large systems)

NOTE 1 Forced circulation systems can be classified either as Factory Made or as Custom Built, depending on the market approach chosen by the final supplier.

NOTE 2 Both Factory Made and Custom Built systems are performance tested under the same set of reference conditions as specified in Annex B of the present standard and Annex A of EN 12977-2:2012. In practice, the installation conditions may differ from these reference conditions.

NOTE 3 A Factory Made system for domestic hot water preparation may have an option for space heating, however this option should not be used or considered during testing as a Factory Made system.

Preview

**prEN 12976-2:2014 (E)****1 Scope**

This European Standard specifies test methods for validating the requirements for Factory Made Thermal Solar Heating Systems as specified in EN 12976-1. The standard also includes two test methods for thermal performance characterization by means of whole system testing.

**2 Normative references**

The following referenced documents are indispensable for the application of this European Standard. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 9806, *Thermal solar systems and components – Factory made systems – Part 2: Test methods*

EN 12976-1:2006, *Thermal solar systems and components - Factory made systems – Part 1: General requirements*

EN 12977-2:2012, *Thermal solar systems and components — Custom built systems — Part 2: Test methods*

EN 60335-1, *Household and similar electrical appliances - Safety - Part 1: General requirements (IEC 60335-1:2001, modified)*

EN 60335-2-21, *Household and similar electrical appliances - Safety - Part 2-21: Particular requirements for storage water heaters (IEC 60335-2-21:2002, modified)*

EN ISO 9488:1999, *Solar energy – Vocabulary (ISO 9488:1999)*

ISO 9459-1:1993, *Solar heating - Domestic water heating systems - Part 1: Performance rating procedure using indoor test methods*

ISO 9459-2:1995, *Solar heating – Domestic water heating systems – Part 2: Outdoor test methods for system performance characterization and yearly performance prediction of solar-only systems*

ISO 9459-5:2007, *Solar heating – Domestic water heating systems – Part 5: System performance characterization by means of whole-system tests and computer simulation*

**3 Terms and definitions**

For the purposes of this European Standard, the terms and definitions given in EN ISO 9488:1999 and EN 12976-1:2006 apply.



## 4 Symbols and abbreviations

$Q_{aux, net}$	net auxiliary energy demand of a solar heating system delivered by the auxiliary heater to the store or directly to the distribution system (see 5.8.3.2)
$Q_d$	heat demand
$Q_L$	energy delivered at the outlet of the solar heating system
$Q_{par}$	parasitic energy (electricity) for the collector loop pump(s) and control unit
$H_c$	hemispherical solar irradiation in the collector plane
$Q_l$	store heat loss
$Q_{ohp}$	heat diverted from the store as active overheating protection, if any
$Q_{sol}$	heat delivered by the collector loop to the store

## 5 Testing

### 5.1 Freeze resistance

#### 5.1.1 General

The following checks are given to ensure that the protective anti-freezing provisions are operating properly. There are many possible forms of protective provisions, and the testing authority shall first identify which method has been employed.

The provision shall then be checked in accordance with the appropriate section of the following list (see 5.1.2 to 5.1.6) in accordance with the manufacturer's recommendations.

#### 5.1.2 Systems using antifreeze fluid

The system components which are exposed to low ambient temperature are filled with an antifreeze fluid, usually a glycol/water mixture, having a low enough freezing point. For thermo-siphon systems declared as freeze resistant down to a specific temperature, one possible test procedure described in AS/NZS 2712 is recommended. This procedure could also be adapted to other systems containing pure water. So far, electrical heater for freeze protection won't be tested for suitability.

For these systems, no freezing test is performed. However, if no sufficient data is available on the freezing point of the antifreeze fluid, the freezing point shall be measured and checked against the minimum system temperature as given by the manufacturer.

**NOTE** In general, the minimum allowed temperature of the system is equal to the freezing point of the antifreeze fluid. If the concentration of some antifreeze fluids - like glycol's - exceeds a certain limit, they can freeze without damaging the system. In this case the minimum allowed temperature can be lower than the freezing point of the antifreeze fluid.

Check the freezing point by measuring the glycol concentration (e.g. using a portable refractometer) before and after the over temperature protection test (5.2). The freezing point shall not differ more than 2 °K from the value recommended by the manufacturer in agreement with the local climate (minimum expected air temperature, radiative cooling of the collectors).

The composition of the fluid shall be checked to see whether it is in accordance with the manufacturer's specifications.

**prEN 12976-2:2014 (E)****5.1.3 Drain-back systems**

When freezing danger occurs, the fluid in the system components that is exposed to low ambient temperature, is drained into a storage vessel for subsequent reuse.

The collector loop piping should be in accordance with the manufacturer's recommendations in the installer manual and if there is no instruction, according to reference conditions given in Annex B.

Filling may be observed from the pressure gauge or from water level indicator. Switch the pump on, and observe the pressure gauge or water level indicator. If the system does not include a pressure gauge or level indicator, other means for checking filling provided by the manufacturer shall be used in accordance with the instruction manual.

Drain-back may be observed from the decreasing reading of the pressure gauge or water level indicator. Switch the pump OFF, and observe the pressure gauge or water level indicator. If the system does not include a pressure gauge or level indicator, other means for checking drain-back provided by the manufacturer shall be used in accordance with the instruction manual.

A system in which components and/or piping are subject to damage by freezing shall have the proper fittings, pipe slope and collector design to allow for manual gravity draining and air filling of the affected components and piping. Pipe slope for gravity draining shall be as the manufacturer recommendation or shall have a minimum 2 cm vertical drop for each meter of horizontal length. This also applies to any header pipes or absorber plate riser tubes internal to the collector.

**5.1.4 Drain-down systems**

The fluid in the system components, which are exposed to low ambient temperature, is drained and run to waste when freezing danger occurs.

To perform checks of the drain-down function the collector loop piping should be in accordance with the manufacturer's recommendations in the installer manual and if there is no instruction, according to reference conditions given in Annex B.

In most cases the systems are equipped with a drain-down valve at the bottom and a vacuum relief valve at the top of the fluid circuit.

The proper opening and closing of the vacuum relief valve shall be checked during drain-down operation and after re-filling the system.

If there is a solenoid drain valve independent of the control unit, simulate the opening temperature.

If there is a non-electrically operated freeze-protection valve, a check can be made using a freezing spray. The temperature-sensing element shall be sprayed. The measured temperature of the valve opening is to be compared with the nominal value given by the manufacturer. It is important that the sensing part of the freeze-protection valve be properly placed.

If the system uses an electrically operated freeze-protection valve, drain down shall be checked while interrupting the power.

The drain-down rate shall be measured (e.g. by using a vessel and a stop-watch) and documented during drain-down operation.

**5.1.5 Freeze protection and control functions combined**

For systems where the freeze-protection and control functions are combined, the control unit shall be checked as follows:

Set the simulated temperature of the freeze-protection sensor to a value deactivating the freeze protection. Decrease the simulated temperature slowly. Measure the temperature  $T_{FP}$  (freeze-protection) of the related actuator. Compare it with the nominal value given by the manufacturer.

### 5.1.6 Other systems

For all other systems, the pump control system, drain-down valve or any other freeze protection device or system shall be checked to the manufacturer's specification and the minimum allowed temperature specified by the manufacturer.

For ICS systems, or other SDHW systems with the tank placed outside, special frost resistance tests should be carried out, as described in C.1.

## 5.2 Over temperature protection

### 5.2.1 Purpose

The purpose of this test is to determine whether the solar water heating system is protected against damage and the user is protected from scalding hot water delivery after a period of no hot water draw and failure of electrical power.

### 5.2.2 Apparatus

The following apparatus is required:

- a) A pyranometer having the minimum characteristics specified in ISO 9806, to measure the total short wave radiation from both the sun and the sky or the short wave radiation from a solar simulator lamp if the test is to be conducted inside a solar simulation chamber.
- b) Equipment to measure the temperature, flow rate and volume of hot water drawn from the system.
- c) An outdoor or an indoor test stand for installing the solar hot water system with the collector array at the manufacturer's specified tilt angle.
- d) A temperature and pressure controlled water supply within the range of 5°C to 25 °C and 200kPa to 600 kPa or the manufacturer's maximum working pressure whichever is less.

This test may be conducted using a solar simulator or outdoors.

### 5.2.3 Procedure

The system, both as described in the installation manual and as installed on the test facility, shall be first checked on overheating safety, e.g. if safety valves and other overheating protection devices are present and installed at the right place, if there are no valves between components and relief valves etc. For systems containing antifreeze fluids, it shall be checked whether sufficient precautions have been taken to prevent the antifreeze fluid from deterioration as a result of high temperature conditions (See also 5.6).

Furthermore, if non-metallic materials are used in any circuit, the highest temperature in the circuit shall be measured during the over temperature protection test, for use in the pressure resistance test.

The procedure of testing shall be as follows:

- a) Assemble the solar water heating system according to the installation instructions with the collector array oriented towards solar noon for the outdoor test, or the simulator lamp may be adjusted to normal incidence for the indoor test.
- b) Charge the system from the water supply and, for pressurized storage tanks, maintain the water supply pressure.
- c) Energize the system as per installation instructions.

**prEN 12976-2:2014 (E)**

- d) (i) For the outdoor test, operate the system for a minimum of 4 consecutive days without any hot water withdrawal and until the collector array has been subjected to 2 consecutive days in which the solar irradiation on the plane of the collector array has exceeded  $20 \text{ MJ/m}^2$  per day and the ambient temperature has exceeded  $20 \text{ }^\circ\text{C}$  during solar noon.
- (ii) For the indoor test, operate the system without any hot water withdrawal at an ambient temperature of  $(25 \pm 2) \text{ }^\circ\text{C}$  and a minimum solar lamp irradiance of  $1000 \text{ W/m}^2$  at the plane of the collector array, measured and with a uniformity as specified in ISO 9459-1:1993, 6.3.1.2 for a 5 h period or until the collector array drains.
- e) (i) For the outdoor test, disconnect all electrical power (if there is any) to the system and continue to operate the system until the solar irradiation on the plane of the collector array has exceeded  $20 \text{ MJ/m}^2$  per day or until the load circuit drains.
- (ii) For the indoor test, disconnect all electrical power to the system and subject the system to a solar lamp irradiance of  $1000 \text{ W/m}^2$  at the plane of the collector array for an additional 4 h or until the collector array drains.
- f) Immediately begin to withdraw a volume of water greater than the total volume of water in the system at a rate of  $2 \times 10^{-4} \pm 3 \times 10^{-5} \text{ m}^3/\text{s}$  ( $10 \pm 1 \text{ L/min.}$ )

**5.2.4 Reporting requirements**

The following results shall be reported:

- a) The make and model identification of the system including ancillary scald and over temperature protection devices fitted as well as a physical description of how over temperature protection should work according to the manufacturer's documentation.
- b) The inclination of the collector array.
- c) A record of temperature of the hot water withdrawn from the system versus time and the total volume of water withdrawn. Note the presence of steam if observed.
- d) Details of the condition of the system and individual components following the test or any failure modes during the test with particular regard to any defects which may affect the serviceability of the system such as the swelling of pipes and components or fluid leakages.

**5.3 Pressure resistance****5.3.1 Purpose**

The purpose of this test is to evaluate hydraulic pressure rating of all components and interconnections of a solar water heating system when installed according to the manufacturer's instructions.

**5.3.2 Apparatus**

The apparatus shall consist of the following:

- a) suitable platform and support structure for installation of the system
- b) pressure regulated hydraulic pressure source
- c) pressure gauge suitable to determine the test pressure to within 5 %
- d) bleed valve
- e) isolation valve

# Bestelformulier

# NEN

## Stuur naar:

NEN Standards Products & Services  
t.a.v. afdeling Klantenservice  
Antwoordnummer 10214  
2600 WB Delft

## NEN Standards Products & Services

Postbus 5059  
2600 GB Delft

Vlinderweg 6  
2623 AX Delft

T (015) 2 690 390  
F (015) 2 690 271

[www.nen.nl/normshop](http://www.nen.nl/normshop)

## Ja, ik bestel

\_\_ ex. NEN-EN 12976-2:2014 2e Ontw. en Thermische zonne-energiesystemen en componenten - Fabrieksmatig geproduceerde systemen - Deel 2: Beproevingmethoden

€ 36.24

**Wilt u deze norm in PDF-formaat? Deze bestelt u eenvoudig via [www.nen.nl/normshop](http://www.nen.nl/normshop)**

### Gratis e-mailnieuwsbrieven

Wilt u op de hoogte blijven van de laatste ontwikkelingen op het gebied van normen, normalisatie en regelgeving? Neem dan een gratis abonnement op een van onze e-mailnieuwsbrieven. [www.nen.nl/nieuwsbrieven](http://www.nen.nl/nieuwsbrieven)

### Retourneren

Fax: (015) 2 690 271  
E-mail: [klantenservice@nen.nl](mailto:klantenservice@nen.nl)  
Post: NEN Standards Products & Services,  
t.a.v. afdeling Klantenservice  
Antwoordnummer 10214,  
2600 WB Delft  
(geen postzegel nodig).

## Gegevens

Bedrijf / Instelling

T.a.v.  O M O V

E-mail

Klantnummer NEN

Uw ordernummer  BTW nummer

Postbus / Adres

Postcode  Plaats

Telefoon  Fax

**Factuuradres** (indien dit afwijkt van bovenstaand adres)

Postbus / Adres

Postcode  Plaats

Datum  Handtekening

### Voorwaarden

- De prijzen zijn geldig tot 31 december 2016, tenzij anders aangegeven.
- Alle prijzen zijn excl. btw, verzend- en handelingskosten en onder voorbehoud bij o.m. ISO- en IEC-normen.
- Bestelt u via de normshop een pdf, dan betaalt u geen handeling en verzendkosten.
- Meer informatie: telefoon (015) 2 690 391, dagelijks van 8.30 tot 17.00 uur.
- Wijzigingen en typfouten in teksten en prijsinformatie voorbehouden.
- U kunt onze algemene voorwaarden terugvinden op: [www.nen.nl/leveringsvoorwaarden](http://www.nen.nl/leveringsvoorwaarden).