



Nederlandse norm

NEN-EN 13201-5

(en)

Wegverlichting - Deel 5: Energieprestatie
indicatoren

Road lighting - Part 5: Energy performance
indicators

ICS 93.080.40

januari 2016

Als Nederlandse norm is aanvaard:
 - EN 13201-5:2015, IDT

Normcommissie 351005 "Verlichting"



THIS PUBLICATION IS COPYRIGHT/PROTECTED

DEZE PUBLICATIE IS AUTEURSRECHTELIJK BESCHERMD

Apart from exceptions provided by the law, nothing from this publication may be duplicated and/or published by means of photocopy, microfilm, storage in computer files or otherwise, which also applies to full or partial processing, without the written consent of the Netherlands Standardization Institute.

The Netherlands Standardization Institute shall, with the exclusion of any other beneficiary, collect payments owed by third parties for duplication and/or act in and out of law, where this authority is not transferred or falls by right to the Reproduction Rights Foundation.

Auteursrecht voorbehouden. Behoudens uitzondering door de wet gesteld mag zonder schriftelijke toestemming van het Nederlands Normalisatie-instituut niets uit deze uitgave worden verveelvoudigd en/of openbaar gemaakt door middel van fotokopie, microfilm, opslag in computerbestanden of anderszins, hetgeen ook van toepassing is op gehele of gedeeltelijke bewerking.

Het Nederlands Normalisatie-instituut is met uitsluiting van ieder ander gerechtigd de door derden verschuldigde vergoedingen voor verveelvoudiging te innen en/of daartoe in en buiten rechte op te treden, voor zover deze bevoegdheid niet is overgedragen c.q. rechtens toekomt aan de Stichting Reprerecht.

Although the utmost care has been taken with this publication, errors and omissions cannot be entirely excluded. The Netherlands Standardization Institute and/or the members of the committees therefore accept no liability, not even for direct or indirect damage, occurring due to or in relation with the application of publications issued by the Netherlands Standardization Institute.

Hoewel bij deze uitgave de uiterste zorg is nagestreefd, kunnen fouten en onvolledigheden niet geheel worden uitgesloten. Het Nederlands Normalisatie-instituut en/of de leden van de commissies aanvaarden derhalve geen enkele aansprakelijkheid, ook niet voor directe of indirecte schade, ontstaan door of verband houdend met toepassing van door het Nederlands Normalisatie-instituut gepubliceerde uitgaven.

EUROPEAN STANDARD

EN 13201-5

NORME EUROPÉENNE

EUROPÄISCHE NORM

December 2015

ICS 93.080.40

English Version

Road lighting - Part 5: Energy performance indicatorsÉclairage public - Partie 5: Indicateurs de performance
énergétiqueStraßenbeleuchtung - Teil 5:
Energieeffizienzindikatoren

This European Standard was approved by CEN on 6 June 2015.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

European foreword.....	4
Introduction.....	5
1 Scope.....	6
2 Normative references.....	6
3 Terms, definitions, symbols and abbreviations.....	6
3.1 Terms and definitions.....	6
3.2 Symbols and abbreviations.....	7
4 Power Density Indicator (PDI).....	9
4.1 Calculation of the power density indicator.....	9
4.2 Average horizontal illuminance to be used for calculation of the power density indicator.....	9
4.3 System power (P) to be used for calculation of the power density indicator.....	10
4.4 Area (A) to be used for calculation of the power density indicator.....	11
5 Annual Energy Consumption Indicator (AECI).....	11
Annex A (informative) Examples of calculation and typical values of energy performance indicators.....	13
A.1 Examples of operational profiles.....	13
A.1.1 General.....	13
A.1.2 Full power operation.....	13
A.1.3 Multi-power operation.....	14
A.1.4 Operation with vehicle and presence detectors.....	14
A.2 Example of calculation.....	15
A.3 Typical values of energy performance indicators.....	16
A.3.1 General.....	16
A.3.2 Two-lane road for motorized traffic (road profile A).....	17
A.3.3 Road with mixed motorized and pedestrian traffic without sidewalks (road profile B).....	18
A.3.4 Road and sidewalk on the side of lighting arrangement (road profile C).....	19
A.3.5 Road and sidewalk on the opposite side to the lighting arrangement (road profile D).....	20
A.3.6 Road and two sidewalks on both sides (road profile E).....	21
A.3.7 Road and two sidewalks on both sides separated from carriageway by grass strips (road profile F).....	22
A.3.8 Typical values of AECI for different operational profiles.....	22
Annex B (informative) Installation luminous efficacy.....	24
B.1 General.....	24

B.2	Calculation of the correction factor	24
B.3	Calculation of the utilisation	25
B.4	Calculation of the efficiency of luminaires	25
Annex C	(informative) Lighting factor of an installation	26
C.1	Installation lighting factor q_{inst}	26
C.2	Role of q_{inst} in road lighting design aimed at energy saving	26
C.3	Typical values of q_{inst}	26
Annex D	(informative) Presentation of energy performance indicators	27
Bibliography	28

Orbeye
Preview

European foreword

This document (EN 13201-5:2015) has been prepared by Technical Committee CEN/TC 169 “Light and lighting”, the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2016 and conflicting national standards shall be withdrawn at the latest by June 2016.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

EN 13201, *Road lighting* is a series of documents that consists of the following parts:

- *Part 1: Guidelines on selection of lighting classes* [Technical Report];
- *Part 2: Performance requirements*;
- *Part 3: Calculation of performance*;
- *Part 4: Methods of measuring lighting performance*;
- *Part 5: Energy performance indicators* [present document].

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

The purpose of this European Standard is to define energy performance indicators for road lighting installations. The standard introduces two metrics, the power density indicator (PDI) D_P and the annual energy consumption indicator (AECI) D_E that should always be used together.

To quantify the potential savings obtainable from improved energy performance and reduced environmental impact, it is essential to calculate both the power density indicator (D_P) and the annual energy consumption indicator (D_E). In addition, the installation luminous efficacy (η_{inst}) can be used for comparing the energy performances of alternative road lighting installations.

Careful choice of lighting class(es) during the design and specification phase will help to maximize energy savings by ensuring only the necessary levels of illumination provided at the correct times and for the minimum periods necessary. Additional guidance is given in the CEN/TR 13201-1 with regard to the visual needs of road users, e.g. under varying traffic volumes during certain times of night or under varying weather conditions.

During the design phase of a road lighting installation care should be taken to ensure that the design criteria specified in EN 13201-2 are achieved but that excess overlighting is reduced to the minimum technically obtainable. Overlighting can be minimized by the careful selection of the luminaire and light source but the specified lighting class, the designed lighting point spacing and uniformity ratios are all determining factors of the luminous flux emitted by the light source and thus the power of the light source required. However, this precise luminous flux may not, in reality, exist. Where the luminous flux of the light source is greater than that required the designer can by means of continuously variable control gear, compensate for this effect by reducing the luminous flux of the light source to the required level resulting in lower energy consumption. The same principles and control gear can be used to compensate for changes in luminous flux emitted throughout the lifetime of the light sources.

The energy levels calculated using this standard should not be used as a direct input for the calculation of the load on the electrical distribution system. Such calculations are normally based on the energy requirement derived directly from the lighting and electrical design.

Examples of operational profiles and examples of calculation of the energy performance indicators are provided in Annex A. Typical values of energy performance indicators are provided to illustrate the energy performance of recent technological level of luminaires and installations.

Annex B introduces the installation luminous efficacy and its factors as a measure of the influence of various light losses and other parameters.

Lighting factor of an installation, as introduced in Annex C, can be additionally used to characterize the energy performance of road lighting installations independently on the lighting components used. Other factors and parameters having influence to the energy performance, such as the maintenance factor (see CIE 154), can be recognized but are not dealt with in this standard.

Recommendations on presentation of the energy performance indicators are provided in Annex D.

1 Scope

This part of the European Standard defines how to calculate the energy performance indicators for road lighting installations using the calculated power density indicator (PDI) D_P and the calculated annual energy consumption indicator (AECI) D_E . Power density indicator (D_P) demonstrates the energy needed for a road lighting installation, while it is fulfilling the relevant lighting requirements specified in EN 13201-2. The annual energy consumption indicator (D_E) determines the power consumption during the year, even if the relevant lighting requirements change during the night or seasons.

These indicators may be used to compare the energy performance of different road lighting solutions and technologies for the same road lighting project. The energy performance of road lighting systems with different road geometries or different lighting requirements cannot be compared to each other directly, as the energy performance is influenced by, amongst others, the geometry of the area to be lit, as well as the lighting requirements. The power density indicator (D_P) and annual energy consumption indicator (D_E) apply for all traffic areas covered by the series of lighting classes M, C and P as defined in EN 13201-2.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 12665:2011, *Light and lighting — Basic terms and criteria for specifying lighting requirements*

EN 13201-2, *Road lighting — Part 2: Performance requirements*

EN 13201-3:2015, *Road lighting — Part 3: Calculation of performance*

3 Terms, definitions, symbols and abbreviations

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 12665:2011 and the following apply.

3.1.1

system power (of a lighting installation in a given state of operation)

P

total power of the road lighting installation needed to fulfil the required lighting classes as specified in EN 13201-2 in all the relevant sub-areas, and to operate and control the lighting installation (unit: W)

3.1.2

power density indicator PDI (of a lighting installation in a given state of operation)

D_P

value of the system power divided by the value of the product of the surface area to be lit and the calculated maintained average illuminance value on this area according to EN 13201-3 (unit: $W \cdot lx^{-1} \cdot m^{-2}$)

3.1.3

annual energy consumption indicator AECI (of a lighting installation in a specific year)

D_E

total electrical energy consumed by a lighting installation day and night throughout a specific year in proportion to the total area to be illuminated by the lighting installation (unit: Wh·m⁻²)

3.1.4

installation luminous efficacy

η_{inst}

minimum luminous flux needed to provide the minimum lighting level for the specified area divided by the total average power consumption of the lighting installation (unit: lm·W⁻¹)

3.1.5

constant light output CLO (of a road lighting installation)

regulation of the road lighting installation aiming at providing a constant light output from the light sources

Note 1 to entry: This functionality aims to compensate for the light loss caused by ageing of the light sources.

3.1.6

installation lighting factor

q_{inst}

dimensionless factor accounting for the relation of the calculated average maintained luminance of road surface over the calculated average maintained horizontal illuminance on this surface and the average luminance coefficient of the table adopted in luminance calculation

3.2 Symbols and abbreviations

Table 1 — Symbols and abbreviations

Symbol or abbreviation	Name or description	Unit
A	Area to be lit	m ²
A_{FL}	Area of the left sidewalk	m ²
A_{FR}	Area of the right sidewalk	m ²
A_R	Area of the carriageway	m ²
AECI	Annual Energy Consumption Indicator	
C_L	Correction factor for luminance or hemispherical illuminance based lighting designs	-
C_{op}	Lighting operation coefficient	-
CLO	Constant Light Output	
D_E	Annual energy consumption indicator (AECI)	Wh·m ⁻²
D_P	Power density indicator (PDI)	W·lx ⁻¹ ·m ⁻²
\bar{E}	Average maintained horizontal illuminance	lx
E_{FL}	Calculated maintained illuminance on the left sidewalk	lx
E_{FR}	Calculated maintained illuminance on the right sidewalk	lx

Bestelformulier

Stuur naar:

NEN Standards Products & Services
t.a.v. afdeling Klantenservice
Antwoordnummer 10214
2600 WB Delft



NEN Standards Products & Services

Postbus 5059
2600 GB Delft

Vlinderweg 6
2623 AX Delft

T (015) 2 690 390
F (015) 2 690 271

www.nen.nl/normshop

Ja, ik bestel

__ ex. NEN-EN 13201-5:2016 en Wegverlichting - Deel 5: Energieprestatie indicatoren € 62.22

Wilt u deze norm in PDF-formaat? Deze bestelt u eenvoudig via www.nen.nl/normshop

Gratis e-mailnieuwsbrieven

Wilt u op de hoogte blijven van de laatste ontwikkelingen op het gebied van normen, normalisatie en regelgeving? Neem dan een gratis abonnement op een van onze e-mailnieuwsbrieven. www.nen.nl/nieuwsbrieven

Gegevens

Bedrijf / Instelling _____

T.a.v. _____ O M O V

E-mail _____

Klantnummer NEN _____

Uw ordernummer _____ BTW nummer _____

Postbus / Adres _____

Postcode _____ Plaats _____

Telefoon _____ Fax _____

Factuuradres (indien dit afwijkt van bovenstaand adres)

Postbus / Adres _____

Postcode _____ Plaats _____

Datum _____ Handtekening _____

Retourneren

Fax: 015 2 690 271

E-mail: klantenservice@nen.nl

Post: NEN Standards Products & Services,

t.a.v. afdeling Klantenservice
Antwoordnummer 10214,
2600 WB Delft

(geen postzegel nodig).

Voorwaarden

- De prijzen zijn geldig tot 31 december 2018, tenzij anders aangegeven.
- Alle prijzen zijn excl. btw, verzend- en handelingskosten en onder voorbehoud bij o.m. ISO- en IEC-normen.
- Bestelt u via de normshop een pdf, dan betaalt u geen handeling en verzendkosten.
- Meer informatie: telefoon 015 2 690 391, dagelijks van 8.30 tot 17.00 uur.
- Wijzigingen en typfouten in teksten en prijsinformatie voorbehouden.
- U kunt onze algemene voorwaarden terugvinden op: www.nen.nl/leveringsvoorwaarden.