

Nederlandse norm

NEN-ISO/IEC 14443-4 (en)

Identification cards - Contactless integrated
circuit cards - Proximity cards - Part 4:
Transmission protocol (ISO/IEC 14443-
4:2016, IDT)

Vervangt NEN-ISO/IEC 14443-4:2008;
NEN-ISO/IEC 14443-4:2008/A1:2012;
NEN-ISO/IEC 14443-4:2008/A2:2012;
NEN-ISO/IEC 14443-3:2011/A3:2014;
NEN-ISO/IEC 14443-4:2008/A4:2014

ICS 35.240.15

juni 2016

Als Nederlandse norm is aanvaard:

- ISO/IEC 14443-4:2016, IDT

Normcommissie 381017 "Identificatie kaarten en persoonlijke identificatie"



THIS PUBLICATION IS COPYRIGHT PROTECTED

DEZE PUBLICATIE IS AUTEURSRECHTELIJK BESCHERMD

Apart from exceptions provided by the law, nothing from this publication may be duplicated and/or published by means of photocopy, microfilm, storage in computer files or otherwise, which also applies to full or partial processing, without the written consent of the Netherlands Standardization Institute.

The Netherlands Standardization Institute shall, with the exclusion of any other beneficiary, collect payments owed by third parties for duplication and/or act in and out of law, where this authority is not transferred or falls by right to the Reproduction Rights Foundation.

Auteursrecht voorbehouden. Behoudens uitzondering door de wet gesteld mag zonder schriftelijke toestemming van het Nederlands Normalisatie-instituut niets uit deze uitgave worden verveelvoudigd en/of openbaar gemaakt door middel van fotokopie, microfilm, opslag in computerbestanden of anderszins, hetgeen ook van toepassing is op gehele of gedeeltelijke bewerking.

Het Nederlands Normalisatie-instituut is met uitsluiting van ieder ander gerechtigd de door derden verschuldigde vergoedingen voor verveelvoudiging te innen en/of daartoe in en buiten rechte op te treden, voor zover deze bevoegdheid niet is overgedragen c.q. rechtens toekomt aan de Stichting Reprorecht.

Although the utmost care has been taken with this publication, errors and omissions cannot be entirely excluded. The Netherlands Standardization Institute and/or the members of the committees therefore accept no liability, not even for direct or indirect damage, occurring due to or in relation with the application of publications issued by the Netherlands Standardization Institute.

Hoewel bij deze uitgave de uiterste zorg is nagestreefd, kunnen fouten en onvolledigheden niet geheel worden uitgesloten. Het Nederlands Normalisatie-instituut en/of de leden van de commissies aanvaarden derhalve geen enkele aansprakelijkheid, ook niet voor directe of indirecte schade, ontstaan door of verband houdend met toepassing van door het Nederlands Normalisatie-instituut gepubliceerde uitgaven.

NEN

©2016 Nederlands Normalisatie-instituut
Postbus 5059, 2600 GB Delft
Telefoon (015) 2 690 390, Fax (015) 2 690 190

Preview

**Identification cards — Contactless
integrated circuit cards — Proximity
cards —**

**Part 4:
Transmission protocol**

*Cartes d'identification — Cartes à circuit intégré sans contact —
Cartes de proximité —*

Partie 4: Protocole de transmission

Copyright
Preview



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	2
5 Protocol activation of PICC Type A	4
5.1 Request for answer to select.....	5
5.2 Answer to select.....	7
5.2.1 Structure of the bytes.....	7
5.2.2 Length byte.....	7
5.2.3 Format byte.....	7
5.2.4 Interface byte TA(1).....	8
5.2.5 Interface byte TB(1).....	9
5.2.6 Interface byte TC(1).....	9
5.2.7 Historical bytes.....	10
5.3 Protocol and parameter selection request.....	10
5.3.1 Start byte.....	10
5.3.2 Parameter 0.....	11
5.3.3 Parameter 1.....	11
5.4 Protocol and parameter selection response.....	11
5.5 Activation frame waiting time.....	12
5.6 Error detection and recovery.....	12
5.6.1 Handling of RATS and ATS.....	12
5.6.2 Handling of PPS request and PPS response.....	12
5.6.3 Handling of the CID during activation.....	13
6 Protocol activation of PICC Type B	13
7 Half-duplex block transmission protocol	13
7.1 Block format.....	14
7.1.1 Length field.....	15
7.1.2 Prologue field.....	15
7.1.3 Information field.....	18
7.1.4 Epilogue field.....	18
7.2 Frame waiting time.....	18
7.3 Frame waiting time extension.....	19
7.4 Power level indication.....	20
7.5 Protocol operation.....	20
7.5.1 S(PARAMETERS) blocks.....	20
7.5.2 Multi-Activation.....	21
7.5.3 Chaining.....	21
7.5.4 Block numbering rules.....	22
7.5.5 Block handling rules.....	23
7.5.6 PICC presence check.....	24
7.5.7 Error detection and recovery.....	24
8 Protocol deactivation of PICC Type A and Type B	25
8.1 Deactivation frame waiting time.....	25
8.2 Error detection and recovery.....	25
9 Activation of bit rates and framing options in the PROTOCOL state	25
10 Frame with error correction	29
Annex A (informative) Multi-Activation example	36

ISO/IEC 14443-4:2016(E)

Annex B (informative) Protocol scenarios	37
Annex C (informative) Block and frame coding overview	46
Annex D (normative) Bit rates of $3fc/4$, fc, $3fc/2$ and $2fc$ from PCD to PICC	48
Annex E (informative) CRC₃₂ encoding	50
Annex F (informative) Frame with error correction	52
Annex G (informative) Framing options	54
Bibliography	55

Forbiede
Preview

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/IEC JTC 1, *Information technology, SC 17, Cards and personal identification*.

This third edition cancels and replaces the second edition (ISO/IEC 14443-4:2008), which has been technically revised. It also incorporates the Amendments ISO/IEC 14443-4:2008/Amd 1:2012, ISO/IEC 14443-4:2008/Amd 2:2012, ISO/IEC 14443-4:2008/Amd 3:2013 and ISO/IEC 14443-4:2008/Amd 4:2014.

ISO/IEC 14443 consists of the following parts, under the general title *Identification cards — Contactless integrated circuit cards — Proximity cards*:

- *Part 1: Physical characteristics*
- *Part 2: Radio frequency power and signal interface*
- *Part 3: Initialization and anticollision*
- *Part 4: Transmission protocol*

ISO/IEC 14443-4:2016(E)**Introduction**

ISO/IEC 14443 is one of a series of International Standards describing the parameters for identification cards as defined in ISO/IEC 7810, and the use of such cards for international interchange.

The protocol, as defined in this part of ISO/IEC 14443, is capable of transferring the application protocol data units as defined in ISO/IEC 7816-4. Thus, application protocol data units may be mapped as defined in ISO/IEC 7816-4 and application selection may be used as defined ISO/IEC 7816-5.

ISO/IEC 14443 is intended to allow operation of proximity cards in the presence of other contactless cards conforming to ISO/IEC 10536 and ISO/IEC 15693 and near field communication (NFC) devices conforming to ISO/IEC 18092 and ISO/IEC 21481.

The International Organization for Standardization (ISO) and International Electrotechnical Commission (IEC) draw attention to the fact that it is claimed that compliance with this International Standards may involve the use of patents.

Copyright
Preview

Identification cards — Contactless integrated circuit cards — Proximity cards —

Part 4: Transmission protocol

1 Scope

This part of ISO/IEC 14443 specifies a half-duplex block transmission protocol featuring the special needs of a contactless environment and defines the activation and deactivation sequence of the protocol.

This part of ISO/IEC 14443 is intended to be used in conjunction with other parts of ISO/IEC 14443 and is applicable to proximity cards or objects of Type A and Type B.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 7816-3, *Identification cards — Integrated circuit cards — Part 3: Cards with contacts — Electrical interface and transmission protocols*

ISO/IEC 7816-4, *Identification cards — Integrated circuit cards — Part 4: Organization, security and commands for interchange*

ISO/IEC 14443-2, *Identification cards — Contactless integrated circuit cards — Proximity cards — Part 2: Radio frequency power and signal interface*

ISO/IEC 14443-3, *Identification cards — Contactless integrated circuit cards — Proximity cards — Part 3: Initialization and anticollision*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

bit duration

one elementary time unit (etu), calculated by the following formula:

$$1 \text{ etu} = 128 / (D \times fc)$$

the initial value of the divisor D is 1, giving the initial etu as follows:

$$1 \text{ etu} = 128 / fc$$

where fc is the carrier frequency as defined in ISO/IEC 14443-2

ISO/IEC 14443-4:2016(E)**3.2
block**

special type of frame, which contains a valid protocol data format

Note 1 to entry: A valid protocol data format includes I-blocks, R-blocks or S-blocks.

**3.3
invalid block**

type of frame, which contains an invalid protocol format

Note 1 to entry: A time-out, when no frame has been received, is not interpreted as an invalid block.

**3.4
frame**

sequence of bits as defined in ISO/IEC 14443-3

Note 1 to entry: The PICC independent from its type may use the frame with error correction defined in [Clause 10](#). Alternatively, the PICC Type A can use one of the standard frames defined for Type A and the PICC Type B can use the frame defined for Type B. This Type B frame is called standard frame, too, within this part of ISO/IEC 14443.

4 Symbols and abbreviated terms

For the purposes of this part of ISO/IEC 14443, the following symbols and abbreviated terms apply.

A	Hamming control bits generation matrix (6 rows, 56 columns)
ACK	positive ACKnowledgement
ATS	Answer To Select
ATQA	Answer To reQuest, Type A
ATQB	Answer To reQuest, Type B
CID	Card IDentifier
CRC	Cyclic Redundancy Check as defined for each PICC Type in ISO/IEC 14443-3
CRC1	most significant byte of CRC (b16 to b9)
CRC2	least significant byte of CRC (b8 to b1)
CRC_32	Cyclic Redundancy Check error detection code used within enhanced block
c_n	Hamming control bit n
<i>d</i>	vector containing 56 data bits
d_n	data bit n
D	Divisor
DR	Divisor Receive (PCD to PICC)
DRI	Divisor Receive Integer (PCD to PICC)
DS	Divisor Send (PICC to PCD)
DSI	Divisor Send Integer (PICC to PCD)
EDC	Error Detection Code
etu	elementary time unit
<i>fc</i>	carrier frequency
FSC	Frame Size for proximity Card
FSCI	Frame Size for proximity Card Integer
FSD	Frame Size for proximity coupling Device
FSDI	Frame Size for proximity coupling Device Integer
FWI	Frame Waiting time Integer
FWT	Frame Waiting Time

FWT_{TEMP}	temporary Frame Waiting Time
\mathbf{H}	matrix needed to calculate Hamming syndrome \underline{s} (6 rows, 62 columns)
$h'_{m,n}$	element in row m and column n of matrix \mathbf{H}'
\mathbf{H}'	matrix needed to get matrix \mathbf{A} (6 rows, 62 columns)
\underline{h}'_n	column vector of matrix \mathbf{H}'
HLTA	HALT Command, Type A
$\mathbf{I}_{6 \times 6}$	6 by 6 Identity matrix
I-block	Information block
INF	INformation field
LEN	two bytes LENGTH field used within enhanced block
m	row index
MAX	index to define a MAXimum value
MIN	index to define a MINimum value
n	column index
NAD	Node ADDRESS
NAK	Negative Acknowledgement
OSI	Open Systems Interconnection
PCB	Protocol Control Byte
PCD	Proximity Coupling Device
PICC	Proximity Card or Object
PPS	Protocol and Parameter Selection
PPSS	Protocol and Parameter Selection Start
PPS0	Protocol and Parameter Selection parameter 0
PPS1	Protocol and Parameter Selection parameter 1
R-block	Receive ready block
R(ACK)	R-block containing a positive acknowledge
R(NAK)	R-block containing a negative acknowledge
RATS	Request for Answer To Select
REQA	REQuest Command, Type A
RFU	Reserved for Future Use by ISO/IEC
\underline{s}	6-bit vector containing Hamming syndrome
s'	error position code
s	error position
S-block	Supervisory block
SAK	Select Acknowledge
SFGI	Start-up Frame Guard time Integer
SFGT	Start-up Frame Guard Time
SYNC	SYNChronization sequence
WUPA	Wake-UP command, Type A
WTX	Waiting Time eXtension
WTXM	Waiting Time eXtension Multiplier
\underline{y}	64-bit vector (\underline{y}' with no padding bits)
\underline{y}'	64-bit vector containing received modified Hamming sub-block
y'_n	received bit n in each modified Hamming sub-block

ISO/IEC 14443-4:2016(E)

For the purposes of this part of ISO/IEC 14443, the following notations apply.

- (xxxxx)b data bit representation;
- 'XY' hexadecimal notation, equal to XY to the base 16.

5 Protocol activation of PICC Type A

The following activation sequence shall be applied.

- PICC activation sequence as defined in ISO/IEC 14443-3 (request, anticollision loop and select).
- The SAK byte shall be checked to get information if the PICC is compliant with ISO/IEC 14443-4. The SAK byte is defined in ISO/IEC 14443-3.
- The PICC may be set to HALT state, using the HLTA Command as defined in ISO/IEC 14443-3, if e.g. no ISO/IEC 14443-4 protocol is used at the PCD.

NOTE The PCD cannot continue the activation sequence in that case.

- If the PICC is compliant to ISO/IEC 14443-4, the RATS may be sent by the PCD as next command after receiving the SAK.
- The PICC shall send its ATS as answer to the RATS. The PICC shall only answer to the RATS if the RATS is received directly after the selection.
- If the PICC supports any changeable parameters in the ATS, a PPS request may be used by the PCD as the next command after receiving the ATS to change parameters.
- The PICC shall send a PPS Response as answer to the PPS request.

A PICC does not need to implement the PPS, if it does not support any changeable parameters in the ATS.

The PCD activation sequence for a PICC Type A is shown in [Figure 1](#).

Bestelformulier

NEN

Stuur naar:

NEN Standards Products & Services
t.a.v. afdeling Klantenservice
Antwoordnummer 10214
2600 WB Delft

NEN Standards Products & Services

Postbus 5059
2600 GB Delft

Vlinderweg 6
2623 AX Delft

T (015) 2 690 390
F (015) 2 690 271

www.nen.nl/normshop

Ja, ik bestel

__ ex. NEN-ISO/IEC 14443-4:2016 en

€ 161.21

Wilt u deze norm in PDF-formaat? Deze bestelt u eenvoudig via www.nen.nl/normshop

Gratis e-mailnieuwsbrieven

Wilt u op de hoogte blijven van de laatste ontwikkelingen op het gebied van normen, normalisatie en regelgeving? Neem dan een gratis abonnement op een van onze e-mailnieuwsbrieven. www.nen.nl/nieuwsbrieven

Retourneren

Fax: (015) 2 690 271
E-mail: klantenservice@nen.nl
Post: NEN Standards Products & Services,
t.a.v. afdeling Klantenservice
Antwoordnummer 10214,
2600 WB Delft
(geen postzegel nodig).

Gegevens

Bedrijf / Instelling

T.a.v. _____ O M O V

E-mail

Klantnummer NEN

Uw ordernummer _____ BTW nummer _____

Postbus / Adres

Postcode _____ Plaats _____

Telefoon _____ Fax _____

Factuuradres (indien dit afwijkt van bovenstaand adres)

Postbus / Adres

Postcode _____ Plaats _____

Datum _____ Handtekening _____

Voorwaarden

- De prijzen zijn geldig tot 31 december 2016, tenzij anders aangegeven.
- Alle prijzen zijn excl. btw, verzend- en handelingskosten en onder voorbehoud bij o.m. ISO- en IEC-normen.
- Bestelt u via de normshop een pdf, dan betaalt u geen handeling en verzendkosten.
- Meer informatie: telefoon (015) 2 690 391, dagelijks van 8.30 tot 17.00 uur.
- Wijzigingen en typfouten in teksten en prijsinformatie voorbehouden.
- U kunt onze algemene voorwaarden terugvinden op: www.nen.nl/leveringsvoorwaarden.