
**Soil quality — Determination
of perchlorate in soil using ion
chromatography**

*Qualité du sol — Détermination du perchlorate des sols en utilisant la
chromatographie ionique*

Preview

Dit document mag slechts op een stand-alone PC worden geïnstalleerd. Gebruik op een netwerk is alleen toestaan als een aanvullende licentieovereenkomst voor netwerkgebruik met NEN is afgesloten. This document may only be used on a stand-alone PC. Use in a network is only permitted when a supplementary license agreement for us in a network with NEN has been concluded.



Reference number
ISO 20295:2018(E)

© ISO 2018

Copyright
Preview



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	1
5 Interferences	2
6 Reagents	2
7 Apparatus	5
8 Procedure	5
8.1 Pre-treatments.....	5
8.2 Extraction.....	5
8.3 Ion chromatography.....	6
8.3.1 General.....	6
8.3.2 Calibration.....	6
8.3.3 Measurement of perchlorate.....	6
9 Quality control	7
9.1 Performance of the separator column.....	7
9.2 Validity check of the calibration function.....	8
10 Calculation	8
11 Expression of results	8
12 Test report	9
Annex A (informative) Example of ion chromatography conditions and the selection of extraction method	10
Annex B (informative) Results of interlaboratory validation study	13
Annex C (informative) Elimination of dissolved sulfate, chloride, hydrogen carbonate, carbonate and metals	17
Annex D (informative) Determination of perchlorate using inline matrix elimination and applying re-injection analysis	20
Annex E (informative) Determination of perchlorate using inline matrix elimination and concentration applying two dimensional ion chromatography (2D)	23
Bibliography	27

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 190, *Soil quality*, Subcommittee SC 3, *Chemical and physical characterization*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Although perchlorate occurs naturally, it is mainly a manmade anion (ClO_4^-). Usually, it is combined with NH_4^+ , Na^+ and K^+ to form ammonium perchlorate, potassium perchlorate, and sodium perchlorate, respectively. It was reported that more than 90 % of perchlorate is used in military activities. Due to the excellent oxidizing capacity of perchlorate, it is added into propellant of rocket, missile, and satellite. We can presume some routes of manmade perchlorate exposure to soil and groundwater. For example, complete or incomplete explosion of the signal bomb (containing about 2 000 μg of perchlorate) in target or impact area, oversupplying of perchlorate for complete combustion in firing point, grand scale of fireworks could be the route of perchlorate exposure to soil and groundwater. In addition to these, other route could come from waste treatment process. Because perchlorate in missile is naturally deteriorated according to time, it should be recharged with a new one. In the past, incineration was preferred for the treatment of deteriorated perchlorate. When the incineration process was carried out in open space and kept as ash on site without any caution, it could be an important route of soil and groundwater contamination. Perchlorate is very stable in water and is not adsorbed easily on soil particle. From that view, surface water or groundwater could be contaminated more often than soil due to surface runoff or leaching process. However, perchlorate can also contaminate soil and vegetation. This kind of contamination could affect high level organisms in food chain. Perchlorate contamination of drinking water and food chain potentially affect human health because it can interfere with iodide uptake by the thyroid gland. Through this kind of interference, thyroid hormone production is decreased and it cause hyperthyroidism. The permitted level of perchlorate concentration in drinking water is below 15 ppb in Korea. Some states in the USA have an advisory level for perchlorate in drinking water. It is very difficult to find a country to regulate perchlorate level in soil because it seems that perchlorate contamination of soil is very rare in normal areas. However, perchlorate could be one of the major contaminants at a target area or firing point in military field and it is needed to manage the perchlorate concentration of soil to protect the vegetation, surface water, and groundwater. For this purpose, a standard method for perchlorate analysis in soil has been developed.

Voorbeeld
Preview

Soil quality — Determination of perchlorate in soil using ion chromatography

1 Scope

This document specifies a method for the determination of perchlorate in soil and soil materials.

Under the conditions specified in this document, a concentration as low as 0,1 mg/kg can be determined.

The working range is restricted by the ion-exchange capacity of the separator column. Dilution of the water extracts to the working range can be necessary.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8466-1, *Water quality — Calibration and evaluation of analytical methods and estimation of performance characteristics — Part 1: Statistical evaluation of the linear calibration function*

ISO 8466-2, *Water quality — Calibration and evaluation of analytical methods and estimation of performance characteristics — Part 2: Calibration strategy for non-linear second-order calibration functions*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

4 Principle

A dried and sieved soil sample is used as the test portion. Perchlorate is extracted by distilled or deionised water from the soil sample. Extraction is conducted by mechanical shaking and centrifugation.

After filtering the extract with a 0,45 µm membrane filter (e.g. cellulose acetate, hydrophilic polypropylene or polyethersulphone filter), the filtrate is analysed by ion chromatography to determine perchlorate.

If the adverse effects of anions, cations or organics are not negligible, appropriate pre-treatment for the elimination of these effects should be applied. Selective removal of interfering elements using a cartridge is one of the applicable pre-treatments.

The method requires the application of high-capacity separator columns, which allow the injection of sample volumes up to 1 ml.

Perchlorate is separated by ion chromatography (IC). Detection is conducted by suppressed conductivity (CD).

An anion-exchange resin is used as the stationary phase and an aqueous solution of salts of weak monobasic acids and dibasic acids is used as an eluent for isocratic or gradient elution (e.g. carbonate-, hydrogen carbonate-, hydroxide-eluent, and organic modifiers such as acetone, acetonitrile).

The concentration of perchlorate is determined after calibration of the overall procedure according to ISO 8466-1 or ISO 8466-2.

Control experiments are necessary to check the validity of the calibration function. Replicate determinations can be necessary. Use of a standard addition method can be required if matrix interferences are expected.

NOTE The results of interlaboratory validation study can be found in [Annex B](#).

5 Interferences

Any substance that has a retention time coinciding with perchlorate and producing a detector response can interfere. Co-elution can be solved by changing columns, eluent strength (e.g. gradient elution), modifying the eluent with organic solvents or by selective removal of the interference with sample pre-treatment.

In the case of saline soil, a high concentration of chloride, sulfate, and carbonate in soil extracts can cause interference with the determination of perchlorate. It was reported that an injection of 800 mg/l of chloride, sulfate, and carbonate (about 6 mS/cm as of electrical conductivity) in perchlorate standard solution (0,025 mg/l) resulted in 80 % of recovery for perchlorate (1). Additionally, metals like iron or aluminium in soil extracts can have adverse effects on the performance of ion chromatograph due to binding with the resin material of the separator or suppressor column. These interference can be reduced by sample dilution, with the aid of special cation exchangers (e.g. Na-form, Ag-form, Ba-form, H-form) or resolved by the application of advanced inline cutting or re-injection techniques (see [Annexes C, D and E](#)).

Users of this document's method should check their system individually for the significant interfering concentration of anions and cations.

In case of agricultural soil containing phosphate fertilizer, pyrophosphate ($P_2O_7^{4-}$) or tripolyphosphate ($P_3O_{10}^{5-}$) could be coeluted with perchlorate depending on the conditions of ion chromatography (2). This kind of interference could be avoided by using an optimized eluent.

Clay particles (e.g. aluminosilicates) or organic compounds (e.g. humic acids) can plug the column even though the centrifugation and filtering processes are applied. It is recommended to use a pre-column to protect the analytical separator column.

6 Reagents

Use only reagents of pro-analysis grade free of compounds containing perchlorate. Weigh the reagents with an accuracy of ± 1 % of the nominal mass, unless stated otherwise. Prepare alternative concentrations or volumes of solutions as described in [6.2](#) to [6.9](#), if necessary. Alternatively, use commercially available solutions of the required concentration.

6.1 Water, with a resistivity of $\geq 18,2$ M Ω cm (25 °C).

6.2 Potassium perchlorate, KClO₄.

6.3 Sodium hydrogen carbonate, NaHCO₃.

6.4 Sodium chloride, NaCl.

6.5 Sodium sulfate, Na₂SO₄.

6.6 Sodium nitrate, NaNO_3 .

6.7 Eluents.

6.7.1 General

Degas all eluents used. Take steps to avoid any renewed air pick-up during operation (e.g. by helium sparging and inline degassing).

The choice of eluent (e.g. potassium hydroxide, sodium hydrogen carbonate, sodium carbonate, sodium hydroxide solutions; mixed with organic modifiers if needed) depends on the choice of column and detector. Seek advice from the column supplier. Apply eluents that were prepared manually, automatically or *in situ* electrochemically prepared. The chosen combination of separator column and eluent should conform to the resolution requirements stated in [Clause 9](#). Use eluents as long as the requirements in [8.3.3](#) and in [Clause 9](#) are met.

One example for an appropriate manually prepared eluent is given in [6.7.2](#). Additionally, another example for an appropriate eluent prepared using a generating device is given in [6.7.3](#).

6.7.2 Sodium hydroxide, $\rho(\text{NaOH}) = 65 \text{ mmol/l}$.

Prepare 65 mmol/l of NaOH by putting 5,2 g of 50 % (mass fraction) aqueous NaOH from the middle portion of the reagent bottle into a 1 000 mL volumetric flask containing about 500 ml of degassed water. Fill it up to the mark with degassed water. Mix this solution gently and degas by sparging with argon or helium or sonicating under a vacuum for 10 min. For the preparation of 50 % (mass fraction) aqueous NaOH, weigh 50 g of sodium hydroxide and transfer into a 100 ml volumetric flask. Dissolve by adding water ([6.1](#)) and fill to the mark with water ([6.1](#)). Do not shake the 50 % (mass fraction) NaOH bottle to avoid forming carbonate.

NOTE Solutions of sodium hydroxide can be susceptible to carbonate contamination resulting from the adsorption of carbon dioxide from the atmosphere. This contamination can lead to irreproducible perchlorate retention times, elevated instrument background conductivity and increased baseline noise/drift.

6.7.3 Potassium hydroxide, $\rho(\text{KOH}) = 65 \text{ mmol/l}$

If the ion chromatographic system has a generating device for KOH eluent, generate 65 mmol/l of KOH eluent according to the manufacturer's recommendations.

Depending on the column's properties the eluent composition can be different. According to the manufacturer's instructions, check which kind of eluent is appropriate for analysing perchlorate.

6.8 Standard solutions.

6.8.1 Perchlorate stock standard solution, $\rho(\text{ClO}_4^-) = 1\,000 \text{ mg/l}$.

Dry potassium perchlorate in the oven at 100 °C for 2 h. Weigh $(1,393 \pm 0,001) \text{ g}$ and transfer quantitatively into a 1 000 ml volumetric flask. Dissolve by adding water ([6.1](#)) and fill to the mark with water ([6.1](#)). Store this stock standard solution in the refrigerator at 2 °C to 8 °C using polyethylene or glass bottles. This stock standard solution is stable for 12 months.

The use of commercially available certified stock standard solution is also possible.

Other alternative perchlorate compounds (e.g. sodium perchlorate, ammonium perchlorate) may also be used in the preparation of (stock) standard solution.

ALTIJD DE ACTUELE NORM IN UW BEZIT HEBBEN?

Nooit meer zoeken in de systemen en uzelf de vraag stellen:
“Is ISO 20295:2018 en de laatste versie?”™

Via het digitale platform NEN Connect heeft u altijd toegang tot de meest actuele versie van deze norm. Vervallen versies blijven ook beschikbaar. **U en uw collega's** kunnen de norm via NEN Connect makkelijk raadplagen, online en offline.

Kies voor slimmer werken en bekijk onze mogelijkheden op www.nenconnect.nl.

Heeft u vragen?

Onze Klantenservice is bereikbaar maandag tot en met vrijdag, van 8.30 tot 17.00 uur.

Telefoon: 015 2 690 391

E-mail: klantenservice@nen.nl

