

---

---

**Simplified structural design for  
reinforced concrete wall buildings**

Preview

Dit document mag slechts op een stand-alone PC worden geïnstalleerd. Gebruik op een netwerk is alleen toestaan als een aanvullende licentieovereenkomst voor netwerkgebruik met NEN is afgesloten. This document may only be used on a stand-alone PC. Use in a network is only permitted when a supplementary license agreement for us in a network with NEN has been concluded.



Reference number  
ISO 18408:2019(E)

© ISO 2019

Copyright  
Preview



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Fax: +41 22 749 09 47  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
<b>Foreword</b> .....	<b>vi</b>
<b>Introduction</b> .....	<b>vii</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Symbols</b> .....	<b>3</b>
<b>5 Materials for reinforced concrete</b> .....	<b>6</b>
5.1 General.....	6
5.2 Cement.....	6
5.3 Aggregates.....	6
5.4 Water.....	6
5.5 Admixtures.....	6
5.6 Storage of materials.....	6
5.7 Steel reinforcement.....	6
5.8 Deformed reinforcement.....	6
5.9 Welded-wire fabric.....	6
5.10 Plain reinforcement.....	6
5.11 Concrete mixture specification.....	7
<b>6 Design and construction procedure</b> .....	<b>7</b>
6.1 Procedure.....	7
6.2 Limit states.....	8
6.3 Ultimate limit state design format.....	9
6.3.1 General.....	9
6.3.2 Required factored strength.....	9
6.3.3 Design strength.....	9
6.4 Serviceability limit state design format.....	9
6.5 Design documentation.....	10
6.5.1 General.....	10
6.5.2 Calculation memoir.....	10
6.5.3 Geotechnical report.....	10
6.5.4 Structural drawings.....	10
6.5.5 Specifications.....	10
<b>7 Limitations</b> .....	<b>11</b>
7.1 General.....	11
7.2 Occupancy.....	11
7.3 Maximum number of storeys.....	11
7.4 Maximum storey height.....	11
7.5 Minimum wall area ratio.....	11
7.6 Upper limit of average shear stress.....	11
7.7 Maximum storey drift angle.....	11
<b>8 Specific requirements</b> .....	<b>12</b>
8.1 Structural systems.....	12
8.1.1 Floor system.....	12
8.1.2 Vertical supporting elements.....	12
8.1.3 Foundation.....	12
8.1.4 Lateral load resisting system.....	12
8.1.5 Other structural elements.....	12
8.2 General program.....	12
8.2.1 Architectural program.....	12
8.2.2 General structural requirements for the project.....	13
8.3 Structural layout.....	13

8.3.1	General structural layout	13
8.3.2	Floor planning of bearing walls	13
8.3.3	Elevation planning of bearing walls	14
<b>9</b>	<b>Actions (loads)</b>	<b>16</b>
9.1	General	16
9.1.1	Load factors and load combinations	16
9.2	Mass of materials	18
9.3	Dead loads	18
9.4	Live loads	19
9.5	Specified snow load	19
9.6	Specified wind forces	19
9.7	Specified earthquake forces	19
9.7.1	General	19
9.7.2	Seismic hazard	20
9.7.3	No seismic hazard zones:	20
9.7.4	Low seismic hazard zones:	20
9.7.5	Intermediate seismic hazard zones:	20
9.7.6	High seismic hazard zones:	20
9.7.7	Soil profile types	26
9.7.8	Site effects	27
9.7.9	Design response spectral ordinates	27
9.8	Seismic design base shear	27
9.8.1	Seismic-resistant structural system	27
9.8.2	Energy-dissipation capacity of the seismic-resistant structural system	28
9.8.3	Computation of the seismic design base shear	28
9.8.4	Vertical distribution of the design seismic forces and the design storey shear forces	28
<b>10</b>	<b>Analysis</b>	<b>28</b>
10.1	Method of analysis for moment, shear and axial force of members	28
10.1.1	General	28
10.1.2	Simplified method	29
10.2	Method of analysis for storey drift angle	33
10.2.1	General	33
10.2.2	Simplified method	33
<b>11</b>	<b>Structural concrete walls</b>	<b>34</b>
11.1	General	34
11.2	Design load definition	34
11.3	Dimensional guides	34
11.3.1	General	34
11.3.2	Limiting dimensions	34
11.4	Details of reinforcement	35
11.4.1	General	35
11.4.2	Shear reinforcement	36
11.4.3	Flexural reinforcement	37
<b>12</b>	<b>Wall girders</b>	<b>38</b>
12.1	General	38
12.2	Design strength	38
12.2.1	Flexural strength	38
12.2.2	Shear strength	38
12.3	Details of reinforcement	39
12.3.1	General	39
12.3.2	Vertical reinforcement	39
12.3.3	Longitudinal reinforcement	40
<b>13</b>	<b>Wall — Wall girder joints</b>	<b>41</b>
13.1	General	41
13.2	Design strength	41

13.3	Development length for reinforcing bars.....	42
13.4	Details of reinforcement.....	43
<b>14</b>	<b>Floor slab.....</b>	<b>43</b>
14.1	General.....	43
14.2	Design load definition.....	43
14.2.1	Loads to be included.....	43
14.2.2	Dead load and live load.....	43
14.2.3	Factored design load.....	43
14.3	Two-way solid slabs supported on wall girders or structural concrete walls.....	43
14.3.1	Dimensional guides.....	43
14.3.2	Design strength.....	44
14.3.3	Design bending moment.....	45
14.4	End anchorage of reinforcement.....	46
<b>15</b>	<b>General reinforced concrete requirements.....</b>	<b>46</b>
15.1	General.....	46
15.2	Cover concrete depth.....	46
15.2.1	Minimum concrete cover.....	46
15.2.2	Special fire protection.....	48
15.2.3	Special corrosion protection.....	48
15.3	Minimum and maximum reinforcement bar diameter.....	48
15.4	Minimum reinforcement bend diameter.....	49
15.5	Standard hook dimensions.....	49
15.6	Bar separation and maximum aggregate size.....	50
15.6.1	General.....	50
15.6.2	Maximum nominal coarse aggregate size.....	50
15.6.3	Minimum clear spacing between parallel bars in a layer.....	51
15.6.4	Minimum clear spacing between parallel layers of reinforcement.....	51
15.6.5	Clear spacing between parallel lap splices.....	51
15.7	Development length, lap splicing and anchorage of reinforcement.....	51
15.7.1	Development length.....	51
15.7.2	Lap splice dimensions.....	53
15.7.3	Minimum standard hook anchorage distance.....	54
<b>16</b>	<b>Foundations.....</b>	<b>54</b>
16.1	Dimensioning of the foundation elements.....	54
16.2	Footings.....	55
16.2.1	Moment in footings.....	55
16.2.2	Shear in footings.....	55
16.2.3	Development of reinforcement in footings.....	55
16.2.4	Minimum footing depth.....	56
16.2.5	Transfer of forces at base of column, wall or reinforced pedestal.....	56
16.2.6	Sloped or stepped footings.....	56
16.3	Foundation mats.....	56
16.4	Footings on piles.....	56
16.4.1	General.....	56
16.4.2	Anchorage of reinforcement.....	56
16.4.3	Maximum axial stresses.....	56
16.4.4	Reinforcement minimum ratios and lengths.....	57
16.5	Foundation beams.....	57
16.5.1	Dimensional guides.....	57
16.5.2	Longitudinal reinforcement.....	57
16.5.3	Transverse reinforcement.....	57
	<b>Bibliography.....</b>	<b>58</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 71, *Concrete, reinforced concrete and pre-stressed concrete*, Subcommittee SC 5, *Simplified design standard for concrete structures*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

This document aims to provide rules for the design and construction of reinforced concrete (RC) wall structures. The design rules are based on the ratio of wall cross-sectional area to the floor area. Therefore, actions (loads) and simplified analysis procedures are included as well as minimum acceptable construction practice guidelines.

Reinforced concrete wall buildings (WRC) consist of bearing walls, wall girders, slabs, footing girders and foundations. These buildings have excellent seismic performance and fire-resistance and are low-priced construction compared to frame structures. This type of structure is one of the most popular buildings for residential apartment houses in the world.

Structural features of WRC buildings can be summarized as follows:

- high seismic performance (according to the damage of the past earthquakes, the damage ratio of WRC structures is much smaller than that of other types of structures);
- fire resistance (the performance is as good as that of RC buildings);
- economical superiority (bearing walls are as thick as wall girders).

Buildings designed according to this document will consequently:

- a) for moderate earthquake motions, not produce cracks on bearing walls.
- b) for extremely large earthquake motions, prevent from collapse and fall.

The characteristics of this document to achieve the above performances are as follows:

- 1) Prevention of shear cracks developing in bearing walls during moderate earthquake motions

The shear stress intensity in bearing walls during moderate earthquake motions on every storey and in every direction should be less than shear cracking stress of concrete being used, in order not to produce cracks in the bearing walls.

Seismic shear force on every storey and in every direction should be set forth corresponding to moderate earthquake motions.

- 2) Prevention of buildings collapsing during extremely large earthquake motions

The design storey shear force should be set forth corresponding to extremely large earthquake motions. However, this magnitude is reduced, considering the ductility of structures. The reduction value may be about 0,5 for this type of structures. Finally, for example, this magnitude for the first storey almost corresponds to half of the total weight of a building.

In order to secure the structural safety in case of such storey shear, some structural specifications are prescribed in the structural design. The upper limits of average shear stress as well as the maximum storey drift angle are defined in order to control the shearing stress of the wall during the extremely large earthquake motions. That is one of such important specifications. Also, steel bar arrangement specifications and bearing wall arrangement/configuration, etc., are very important specifications to secure structural safety.

This document contains provisions that can be modified by the National Standards Body due to local design and construction requirements and practices. The specifications that can be modified are indicated using [“boxed values”]. The National Standards Body is expected to review the “boxed values” and may substitute alternative definitive values for these elements for use in the national application of this document.

Voorbeeld  
Preview



# Simplified structural design for reinforced concrete wall buildings

## 1 Scope

This document applies to reinforced concrete building consisting of load bearing walls of reinforced concrete buildings [such buildings are called reinforced concrete box-shaped wall buildings and (RC wall building)] or to the part of RC wall building which uses both this and other types of structure.

This document applies to RC wall building as follows:

- RC wall building with 5 or fewer aboveground storeys;
- eaves height of 16 m or less;
- storey height on each storey of 3 m or less;
- on the top storey the storey height can be 3,3 m or less;
- if the roof has a slope, the sum of the storey height of the top storey and the height from the eaves to the ridge of 4 m or less.

Deep foundations, such as piles and caissons, and their pile footings and caps, are beyond the scope of this document, and are not covered by it.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2103, *Loads due to use and occupancy in residential and public buildings*

ISO 2633, *Determination of imposed floor loads in production buildings and warehouses*

ISO 4354, *Wind actions on structures*

ISO 4355, *Bases for design of structures — Determination of snow loads on roofs*

ISO 6935-1, *Steel for the reinforcement of concrete — Part 1: Plain bars*

ISO 6935-2, *Steel for the reinforcement of concrete — Part 2: Ribbed bars*

ISO 6935-3, *Steel for the reinforcement of concrete — Part 3: Welded fabric*

ISO 9194, *Bases for design of structures — Actions due to the self-weight of structures, non-structural elements and stored materials — Density*

ISO 15673, *Guidelines for the simplified design of structural reinforced concrete for buildings*

ISO 28842, *Guidelines for simplified design of reinforced concrete bridges*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions in ISO 28842 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

### 3.1

#### **base**

level of a structure at which earthquake motions are assumed to be imparted to a building

Note 1 to entry: The base does not necessarily coincide with the ground level.

### 3.2

#### **load bearing wall**

wall proportioned to resist combinations of shear, moments, and axial forces

Note 1 to entry: A "shear wall" is a "structural wall."

### 3.3

#### **drift**

difference between the horizontal displacements of two levels

### 3.4

#### **factored load**

specified nominal load multiplied by the appropriate load factor

### 3.5

#### **floor system**

set of structural elements that comprise the floor of a storey in a building

Note 1 to entry: It includes the beams and girders, the joists (if employed), and the slab that spans between them.

### 3.6

#### **foundation girder**

girder that rests on the foundation and spans between footings, used either to support walls or to limit differential settlement of the foundation

### 3.7

#### **hoop**

closed stirrup, tie, or continuously wound spiral

Note 1 to entry: A closed stirrup or tie can be made up of several reinforcement elements, each having seismic hooks at both ends. A continuously wound spiral shall have a seismic hook at both ends.

### 3.8

#### **non-structural element**

set of architectural, mechanical, and electrical components and systems permanently attached to the building

### 3.9

#### **occupancy**

purpose for which a building or other structure, or part thereof, is used or intended to be used

### 3.10

#### **partition**

non-structural wall that is employed to divide spaces

Note 1 to entry: Partitions do not support other parts of the building except themselves. When they are built in the exterior, they are sometimes referred as curtain walls.

### 3.11

#### **slab on grade**

slab set directly on the ground that serves either as an internal traffic surface or as part of the foundation

**3.12****storey height**

vertical distance between the upper part of the slab of a storey and the upper part of the slab of the floor below

**3.13****storey drift angle**

angle of the inter-storey drift divided by the storey height

**3.14****diaphragm**

structural member, such as floor and roof slabs, which transmits inertial induced by earthquake motions

**3.15****wall area ratio**

ratio of the total wall area in each direction to the floor area

**4 Symbols**

Symbol	Description	Unit
$a$	depth of equivalent uniform compressive stress block	mm
$a_m$	acceleration magnifying factor	—
$a_x$	acceleration at floor level	—
$A_a$	effective peak horizontal acceleration coefficient	—
$A_b$	area of an individual reinforcement bar or wire	mm <sup>2</sup>
$A_{fi}$	area of the $i$ -th floor	m <sup>2</sup>
$A_g$	gross area of section of element	mm <sup>2</sup>
$a_t$	area of longitudinal tension reinforcement	mm <sup>2</sup>
$A_w$	area of shear reinforcement within a distance, $s$	mm <sup>2</sup>
$A_{wi}$	sectional area of the structural wall in the $x$ - or $y$ -direction at the $i$ storey	—
$b$	width of the section of the member	mm
$b_f$	effective width of the compression flange in a T shaped section	mm
$d$	effective depth, shall be taken as the distance from extreme compression fibre to centroid of tension reinforcement	mm
$d_b$	nominal diameter of reinforcing bar	mm
$E$	load effects of earthquake, or related internal moments and forces	—
$E_c$	modulus of elasticity of concrete	MPa
$f'_c$	specified compressive strength of concrete	MPa
$\sqrt{f'_c}$	positive square root of specified compressive strength of concrete	MPa
$f_s$	shear strength of concrete	—
$f_y$	specified yield strength of reinforcement, MPa	MPa
$wf_t$	specified yield strength of transverse or spiral reinforcement	—
$F$	loads due to weight and pressures of fluids with well-defined densities and controllable maximum heights, or related internal moments and forces	—
$G_i$	shear modulus of concrete at the $i$ -th storey	—
$h$	depth or thickness of structural element or overall thickness of member	mm
$h_{bi}$	average depth of wall girders in the $x$ - or $y$ -direction at the $i$ -th storey	—
$H_i$	storey height at the $i$ -th storey	—
$h_i$	average height of structural walls in the $x$ - or $y$ -direction at the $i$ -th storey	—
$h_0$	clear vertical distance between lateral supports of columns and walls	mm

Symbol	Description	Unit
$h_w$	height of entire structural concrete wall from base to top	mm
$H$	loads due to the weight and pressure of soil, water in soil, or other materials, or related internal moments and forces	—
$l$	span of structural element or length of span measured centre-to-centre of beams or other supports	—
$l_d$	development length for reinforcing bar	mm
$l_i$	average length of structural walls in the $x$ - or $y$ -direction at the $i$ -th storey	—
$l_w$	horizontal length of structural concrete wall	mm
$L_i$	ratio of the total wall length to the floor area at $i$ -th floor	—
$L_{0i}$	minimum requirement of $L_i$	—
$M$	maximum bending moment in the wall girder	—
${}^D M_A$	design moment due to gravity load	—
$M_{bE}$	moment in of wall girder	—
$M_E$	moment due to seismic load	—
$M_L$	moment due to gravity load	—
$m_w$	mass of the non-structural wall	kg
$M_{bn}$	nominal flexural moment strength at section at balanced conditions	N·mm
$M_{br}$	flexural moment strength at section at balanced conditions	N·mm
$M_n$	nominal flexural moment strength at section	N·mm
$M_r$	flexural moment strength at section	N·mm
$M_u$	factored flexural moment at section	N·mm
$M_u^-$	factored negative flexural moment at section	N·mm
$M_u^+$	factored positive flexural moment at section	N·mm
$n$	design shear margin, which shall be greater or equal to 1.5	—
$P_d$	non-factored dead load axial force at section or non-factored concentrated dead load applied directly to the element	N
$P_n$	nominal axial load strength at section	N
$P_{n(max)}$	maximum compression nominal axial load strength at section	N
$P_{0n}$	axial compressive strength at section	N
$p_w$	hoop ratio ( $0,002 \leq p_w \leq 0,012$ )	—
$P_{wE}$	axial force of structural wall	—
$\Sigma P_u$	sum of all factored concentrated design loads within the span	N
$Q$	maximum shear force in the wall girder	—
$Q_E$	design shear force due to seismic load	—
$Q_L$	design shear force due to gravity load	—
$q_u$	factored load per unit area	N/m <sup>2</sup>
$r_u$	factored uniformly distributed reaction from the slab on the supporting girder, beam or structural concrete wall	N/m
$R$	response modification factor	—
$R_1$	storey drift angle at the first storey	—
$R_i$	storey drift angle at the $i$ -th storey	—
$R_n$	storey drift angle at the top storey	—
$s$	centre-to-centre spacing of transverse reinforcement measured along the axis of the element or spacing between stirrups or vertical spacing between bars of skin reinforcement or spacing of longitudinal or transverse reinforcement or clear distance between webs	mm

# Bestelformulier

## Stuur naar:

NEN Standards Products & Services  
t.a.v. afdeling Klantenservice  
Antwoordnummer 10214  
2600 WB Delft



**NEN** Standards Products & Services

Postbus 5059  
2600 GB Delft

Vlinderweg 6  
2623 AX Delft

T (015) 2 690 390  
F (015) 2 690 271

[www.nen.nl/normshop](http://www.nen.nl/normshop)

## Ja, ik bestel

\_\_ ex. ISO 18408:2019 en

€ 149.56

**Wilt u deze norm in PDF-formaat? Deze bestelt u eenvoudig via [www.nen.nl/normshop](http://www.nen.nl/normshop)**

### Gratis e-mailnieuwsbrieven

Wilt u op de hoogte blijven van de laatste ontwikkelingen op het gebied van normen, normalisatie en regelgeving? Neem dan een gratis abonnement op een van onze e-mailnieuwsbrieven. [www.nen.nl/nieuwsbrieven](http://www.nen.nl/nieuwsbrieven)

## Gegevens

Bedrijf / Instelling \_\_\_\_\_

T.a.v. \_\_\_\_\_ O M O V

E-mail \_\_\_\_\_

Klantnummer NEN \_\_\_\_\_

Uw ordernummer \_\_\_\_\_ BTW nummer \_\_\_\_\_

Postbus / Adres \_\_\_\_\_

Postcode \_\_\_\_\_ Plaats \_\_\_\_\_

Telefoon \_\_\_\_\_ Fax \_\_\_\_\_

**Factuuradres** (indien dit afwijkt van bovenstaand adres)

Postbus / Adres \_\_\_\_\_

Postcode \_\_\_\_\_ Plaats \_\_\_\_\_

Datum \_\_\_\_\_ Handtekening \_\_\_\_\_

### Retourneren

Fax: 015 2 690 271

E-mail: [klantenservice@nen.nl](mailto:klantenservice@nen.nl)

Post: NEN Standards Products & Services,

t.a.v. afdeling Klantenservice  
Antwoordnummer 10214,  
2600 WB Delft

(geen postzegel nodig).

### Voorwaarden

- De prijzen zijn geldig tot 31 december 2018, tenzij anders aangegeven.
- Alle prijzen zijn excl. btw, verzend- en handelingskosten en onder voorbehoud bij o.m. ISO- en IEC-normen.
- Bestelt u via de normshop een pdf, dan betaalt u geen handeling en verzendkosten.
- Meer informatie: telefoon 015 2 690 391, dagelijks van 8.30 tot 17.00 uur.
- Wijzigingen en typfouten in teksten en prijsinformatie voorbehouden.
- U kunt onze algemene voorwaarden terugvinden op: [www.nen.nl/leveringsvoorwaarden](http://www.nen.nl/leveringsvoorwaarden).