

Dit document mag slechts op een stand-alone PC worden geïnstalleerd. Gebruik op een netwerk is alleen toestaan als een aanvullende licentieovereenkomst voor netwerkgebruik met NEN is afgesloten.  
This document may only be used on a stand-alone PC. Use in a network is only permitted when a supplementary license agreement for us in a network with NEN has been concluded.

Vervangt CR 205-009:1996

Nederlandse norm

# **NEN-EN 50090-5-2** (en)

Home and Building Electronic Systems (HBES)  
- Part 5-2: Media and media dependent layers -  
Network based on HBES Class 1, Twisted Pair

ICS 97.120  
maart 2004

Als Nederlandse norm is aanvaard:  
- EN 50090-5-24:2004.IDT

VOORBEELD  
Preview

Normcommissie 381 025 "Telematica Installaties"

---

Apart from exceptions provided by the law, nothing from this publication may be duplicated and/or published by means of photocopy, microfilm, storage in computer files or otherwise, which also applies to full or partial processing, without the written consent of the Netherlands Standardization Institute.

The Netherlands Standardization Institute shall, with the exclusion of any other beneficiary, collect payments owed by third parties for duplication and/or act in and out of law, where this authority is not transferred or falls by right to the Reproduction Rights Foundation.

---

Auteursrecht voorbehouden. Behoudens uitzondering door de wet gesteld mag zonder schriftelijke toestemming van het Nederlands Normalisatie-instituut niets uit deze uitgave worden verveelvoudigd en/of openbaar gemaakt door middel van fotokopie, microfilm, opslag in computerbestanden of anderszins, hetgeen ook van toepassing is op gehele of gedeeltelijke bewerking.

Het Nederlands Normalisatie-instituut is met uitsluiting van ieder ander gerechtigd de door derden verschuldigde vergoedingen voor verveelvoudiging te innen en/of daartoe in en buiten rechte op te treden, voor zover deze bevoegdheid niet is overgedragen c.q. rechtens toekomt aan de Stichting Reprerecht.

---

Although the utmost care has been taken with this publication, errors and omissions cannot be entirely excluded. The Netherlands Standardization Institute and/or the members of the committees therefore accept no liability, not even for direct or indirect damage, occurring due to or in relation with the application of publications issued by the Netherlands Standardization Institute.

---

Hoewel bij deze uitgave de uiterste zorg is nagestreefd, kunnen fouten en onvolledigheden niet geheel worden uitgesloten. Het Nederlands Normalisatie-instituut en/of de leden van de commissies aanvaarden derhalve geen enkele aansprakelijkheid, ook niet voor directe of indirecte schade, ontstaan door of verband houdend met toepassing van door het Nederlands Normalisatie-instituut gepubliceerde uitgaven.

## Nederlands voorwoord

Voor de in deze norm vermelde normatieve verwijzingen bestaan in Nederland de volgende equivalenten:

<u>vermelde norm</u>	<u>Nederlandse norm</u>	<u>titel</u>
EN 50090-1	-	-
EN 50090-2-2	NEN-EN 50090-2-2	Gebouwbeheersystemen (HBES) - Deel 2-2: Systemoverzicht - Algemene technische eisen (en)
EN 50090-3-2:2004	NEN-EN 50090-3-2:2004	Gebouwbeheersystemen (HBES) - Deel 3-2: Toepassingsaspecten - Gebruikersproces voor HBES klasse 1 (en)
EN 50090-4-2:2004	NEN-EN 50090-4-2:2004	Gebouwbeheersystemen (HBES) - Deel 4-2: Media lokale lagen - Transportlaag, netwerklaag en algemene delen van gegevensverbindingslaag voor HBES Klasse 1 (en)
EN 50090-7-1:2004	NEN-EN 50090-7-1:2004	Gebouwbeheersystemen (HBES) - Deel 7-1: Systemmanagement - Management procedures (en)
EN 50090-9-1:2004	-	-
EN 50290: series	-	-
EN 61000-4-5	NEN 11000-4-5	Elektromagnetische compatibiliteit (EMC) - Deel 4: Beproevingen en meettechnieken - Sectie 5: Stootspanningen - Immunitetsproef (en,fr)
EN 61000-6-1	NEN-EN-IEC 61000-6-1	Elektromagnetische compatibiliteit (EMC) - Deel 6-1: Algemene normen - Immunitet voor huishoudelijke, handels- en lichtindustriële omgevingen (en,fr)
EN 61000-6-2	NEN-EN-IEC 61000-6-2	Elektromagnetische compatibiliteit (EMC) - Deel 6-2: Algemene normen - Immunitet voor industriële omgevingen (en,fr)
HD 21.2 S2	-	-
HD 22.2 S2	-	-
IEC 60189-2	-	-
IEC 60332-1	-	-
IEC 60754-2	-	-



EUROPEAN STANDARD

**EN 50090-5-2**

NORME EUROPÉENNE

EUROPÄISCHE NORM

February 2004

ICS 97.120

Supersedes R205-009:1996

English version



**Home and Building Electronic Systems (HBES)  
Part 5-2: Media and media dependent layers -  
Network based on HBES Class 1, Twisted Pair**

Systèmes électroniques pour les foyers  
domestiques et les bâtiments (HBES)  
Partie 5-2: Médias et couches  
dépendantes des médias -  
Réseau basé sur HBES Classe 1,  
Paire Torsadée

Elektrische Systemtechnik für Heim  
und Gebäude (ESHG)  
Teil 5-2: Medien und medienabhängige  
Schichten -  
Netzwerk basierend auf ESHG Klasse 1,  
Twisted Pair

This European Standard was approved by CENELEC on 2003-12-02. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in one official version (English). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official version.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

**CENELEC**

European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**Central Secretariat: rue de Stassart 35, B - 1050 Brussels**

## Contents

Foreword .....	5
Introduction.....	6
1 Scope.....	6
2 Normative references .....	6
3 Terms, definitions and abbreviations .....	7
3.1 Terms and definitions.....	7
3.2 Abbreviations .....	9
4 Requirements for HBES Class 1, Twisted Pair Type 0 (TP0) .....	10
4.1 Datagram service .....	10
4.2 Medium definition.....	14
4.3 Power feeding service.....	16
4.4 Data link layer type Twisted Pair Type 0.....	25
4.5 Full Twisted Pair Type 0 frame structure .....	35
5 Requirements for HBES Class 1, Twisted Pair Type 1 (TP1-64 & TP1-256) .....	36
5.1 Physical layer requirements – Overview.....	36
5.2 Requirements for analogue bus signals.....	38
5.3 Medium attachment unit (MAU) .....	43
5.4 Twisted Pair Type 1 bus cable.....	50
5.5 Topology.....	53
5.6 Services of the physical layer type Twisted Pair Type 1 .....	56
5.7 Behaviour of the physical layer type Twisted Pair Type 1 entity.....	58
5.8 Data link layer type Twisted Pair Type 1.....	58
Figure 1 – NRZ line code .....	11
Figure 2 – Character format.....	11
Figure 3 – Transmitter rising and falling edges.....	12
Figure 4 – Repeater maximum transition time .....	15
Figure 5 – TP0 power supply gauge.....	18
Figure 6 – Power supply dynamic internal resistor measuring test set-up.....	18
Figure 7 – Falling edge and over-current measurements.....	19
Figure 8 – TP0 Network with distributed power supply .....	20
Figure 9 – Voltage / Current gauge of one node.....	21
Figure 10 – Voltage / Current gauge of <u>entire</u> distributed power supply with 6 to 8 supplying nodes.....	24
Figure 11 – Common part of frame structure .....	26
Figure 12 – Control Field .....	26
Figure 13 – CTRL Field .....	27
Figure 14 – Format1s, L_Data_Standard Frame Format with standard field-name abbreviations .....	27
Figure 15 – Format 1e, L_Data_Extended Frame Format with standard fieldname abbreviations .....	28
Figure 16 – EFF field .....	29

Figure 17 – Format 2, Short Acknowledgement frame format .....	30
Figure 18 – Transmission definition .....	35
Figure 19 – Format 1s, Full L_Data_Standard Request frame format .....	35
Figure 20 – Format 1e, Full L_Data_Extended Request frame format .....	36
Figure 21 – Logical structure of physical layer type TP1 .....	38
Figure 22 – Octet mapped to a serial character.....	38
Figure 23 – “1”-Bit frame.....	39
Figure 24 – “0”-Bit frame.....	40
Figure 25 – Delayed logical “0” .....	41
Figure 26 – Overlapping of two logical “0” (example) .....	42
Figure 27 – Method of transmitting.....	45
Figure 28 – Example of transmitter characteristics.....	46
Figure 29 – Example of a diagram of a TP1-64 transmitter.....	46
Figure 30 – Example of a diagram of a TP1-256 transmitter ( $I_{\text{limit}} 0,4 \text{ A}$ ).....	47
Figure 31 – Relation between framed data and asynchronous signal .....	48
Figure 32 – Relation between digital signal and serial bit stream .....	49
Figure 33 – Example of a Light Dimmer .....	50
Figure 34 – Physical Segments .....	53
Figure 35 – Physical segments combined to a line.....	54
Figure 36 – Lines combined to a zone.....	54
Figure 37 – Network topology .....	55
Figure 38 – Control Field .....	59
Figure 39 – Frame Fields with Standard Fieldname Abbreviations .....	59
Figure 40 – Format 1s, L_Data_Standard Frame Format.....	60
Figure 41 – Check octet.....	60
Figure 42 – Frame Fields with Standard Fieldname Abbreviations .....	61
Figure 43 – Format 1e, L_Data_Extended Frame Format.....	61
Figure 44 – Extended Control Field.....	62
Figure 45 – Format 3 - L_Poll_Data request frame format.....	62
Figure 46 – L_Poll_Data response frame format .....	63
Figure 47 – Format 2 - Short Acknowledgement frame format.....	64
Figure 48 – Character timing.....	64
Figure 49 – Priority operation.....	66
Figure 50 – Guarantee of access fairness.....	67
Figure 51 – State machine of data link layer .....	72
Table 1 – Electrical data encoding .....	11
Table 2 – Transceiver characteristics – Sending part.....	12
Table 3 – Transceiver characteristics – Receiving part .....	13
Table 4 – Mandatory and optional requirements for physical layer services .....	13
Table 5 – Ph-Result parameter .....	14
Table 6 – Requirements for the TP0 line.....	15
Table 7 – General hardware requirements .....	16

Table 8 – Current consumption requirements .....	17
Table 9 – Power supply voltage .....	17
Table 10 – Requirements for one supplying DPS device .....	21
Table 11 – Requirements for entire DPS .....	23
Table 12 – Possible cable lengths depending on number of DPS devices connected (for a typical cable) .....	24
Table 13 – Priority of frames – IFT .....	32
Table 14 – Requirements for Acknowledgement wait time, frame re-transmission .....	34
Table 15 – Requirements for full wait time, frame re-transmission .....	34
Table 16 – System parameters of physical layer Type TP1-64 and TP1-256 .....	37
Table 17 – Analogue and digital signal of a logical “1” .....	39
Table 18 – Analogue and digital signal of logical “0” .....	41
Table 19 – Limits within a character .....	42
Table 20 – Unit currents for standard devices .....	44
Table 21 – Dynamic requirements of a TP1-64 transmitter .....	45
Table 22 – Dynamic requirements of a TP1-256 transmitter .....	46
Table 23 – Requirements for the receiver .....	47
Table 24 – Requirements for bit coding .....	48
Table 25 – Requirements for the bit decoding unit .....	49
Table 26 – Requirements for TP1 cable .....	51
Table 27 – Requirements for character coding .....	65
Table 28 – Requirements for character decoding .....	65
Table 29 – Priority sequence, in descending order of importance .....	66



## Foreword

This European Standard was prepared by the Technical Committee CENELEC TC 205, Home and Building Electronic Systems (HBES) with the help of CENELEC co-operation partner Konnex Association (formerly EHBESA).

The text of the draft was submitted to the Unique Acceptance Procedure and was approved by CENELEC as EN 50090-5-2 on 2003-12-02.

This European Standard supersedes R205-009:1996.

CENELEC takes no position concerning the evidence, validity and scope of patent rights.

Konnex Association as Cooperating Partner to CENELEC confirms that to the extent that the standard contains patents and like rights, the Konnex Association's members are willing to negotiate licenses thereof with applicants throughout the world on fair, reasonable and non-discriminatory terms and conditions.

**Konnex Association**

Neerveldstraat, 105

Twin House

B - 1200 Brussels

Tel.: + 32 2 775 85 90

Fax.: + 32 2 675 50 28

e-mail: [info@konnex.org](mailto:info@konnex.org)

[www.konnex.org](http://www.konnex.org)

Attention is drawn to the possibility that some of the elements of this standard may be the subject of patent rights other than those identified above. CENELEC shall not be held responsible for identifying any or all such patent rights.

The following dates were fixed:

- latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2004-12-01
- latest date by which the national standards conflicting with the EN have to be withdrawn (dow) 2006-12-01

EN 50090-5-2 is part of the EN 50090 series of European Standards, which will comprise the following parts:

- Part 1: Standardisation structure
- Part 2: System overview
- Part 3: Aspects of application
- Part 4: Media independent layers
- Part 5: Media and media dependent layers
- Part 6: Interfaces
- Part 7: System management
- Part 8: Conformity assessment of products
- Part 9: Installation requirements

## Introduction

According to OSI Physical Layers consist of the medium, the cable, the connectors, the transmission technology etc. which refers to their hardware requirements. In this European Standard however, the status of the Physical Layer as a “communication medium” is emphasized.

## 1 Scope

This European Standard defines the mandatory and optional requirements for the medium specific physical and data link layer for HBES Class 1 Twisted Pair in its two variations called TP0 and TP1.

Data link layer interface and general definitions, which are media independent, are given in EN 50090-4-2.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50090-1 <sup>1)</sup>	<i>Home and Building Electronic Systems (HBES) – Part 1: Standardisation structure</i>
EN 50090-2-2	<i>Home and Building Electronic Systems (HBES) – Part 2-2: System overview – General technical requirements</i>
EN 50090-3-2:2004	<i>Home and Building Electronic Systems (HBES) – Part 3-2: Aspects of application – User process for HBES Class 1</i>
EN 50090-4-2:2004	<i>Home and Building Electronic Systems (HBES) – Part 4-2: Media independent layers – Transport layer, network layer and general parts of data link layer for HBES Class 1</i>
EN 50090-7-1:2004	<i>Home and Building Electronic Systems (HBES) – Part 7-1: System Management – Management procedures</i>
EN 50090-9-1:2004	<i>Home and Building Electronic Systems (HBES) – Part 9-1: Installation requirements – Generic cabling for HBES Class 1 Twisted Pair</i>
EN 50290 series	<i>Communication cables</i>
EN 61000-4-5	<i>Electromagnetic compatibility (EMC) – Part 4-5: Testing and measurement techniques – Surge immunity test (IEC 61000-4-5)</i>
EN 61000-6-1	<i>Electromagnetic compatibility (EMC) – Part 6-1: Generic standards – Immunity for residential, commercial and light-industrial environments (IEC 61000-6-1, mod.)</i>
EN 61000-6-2	<i>Electromagnetic compatibility (EMC) – Part 6-2: Generic standards - Immunity for industrial environments (IEC 61000-6-2, mod.)</i>
HD 21.2 S2	<i>Polyvinyl chloride insulated cables of rated voltages up to and including 450/750 V – Part 2: Test methods (IEC 60227-2, mod.)</i>

<sup>1)</sup> At draft stage.

HD 22.2 S2	<i>Rubber insulated cables of rated voltages up to and including 450/750 V – Part 2: Test methods (IEC 60245-2, mod.)</i>
IEC 60189-2	<i>Low-frequency cables and wires with PVC insulation and PVC sheath – Part 2: Cables in pairs, triples, quads and quintuples for inside installations</i>
IEC 60332-1	<i>Tests on electric cables under fire conditions – Part 1: Test on a single vertical insulated wire or cable</i>
IEC 60754-2	<i>Test on gases evolved during combustion of electric cables – Part 2: Determination of degree of acidity of gases evolved during the combustion of materials taken from electric cables by measuring pH and conductivity</i>

### 3 Terms, definitions and abbreviations

#### 3.1 Terms and definitions

For the purposes of this part the terms and definitions given in EN 50090-1 and the following apply.

##### 3.1.1

##### **HBES Class 1 Twisted Pair Type 0**

the Twisted Pair medium Twisted Pair Type 0 (TP0) is a physical layer specification for data and power transmission on a single twisted pair, allowing asynchronous character-oriented data transfer in a half duplex bi-directional communication mode, using a specifically unbalanced/unsymmetrical base-band signal coding with collision avoidance under SELV conditions

##### 3.1.2

##### **HBES Class 1 Twisted Pair Type 1**

the Twisted Pair medium Twisted Pair Type 1 (TP1) is a physical layer specification for data and power transmission on a single twisted pair, allowing asynchronous character-oriented data transfer in a half duplex bi-directional communication mode, using a specifically balanced/symmetrical base-band signal coding with collision avoidance under SELV conditions

##### 3.1.3

##### **distributed power supply**

the bus is powered in a distributed way by a number of the devices connected to the line (compared to a centralized power supply)

##### 3.1.4

##### **Logical Tag Extended HEE**

usage of the L\_Data\_Extended frame dedicated to extended group addressing

##### 3.1.5

##### **Remote Powered Devices**

remote Powered Bus Devices (RPD) do not extract their energy for the application circuit and the bus controller from the bus but from another independent source of energy, e.g. mains. Owing to the reduced DC power consumption of RPD, a bus line equipped with such devices requires less power from the installed Power Supply Unit (PSU). The connection of bus-controller and application to the same electrical potential reduces the effort of galvanic separation in RPD

##### 3.1.6

##### **TP0 C Factor**

to simplify system engineering, the supply current of a TP0 device (both power supply and bus device) is expressed by a factor "C", defined as

$$C = \frac{\text{Actual current}}{\text{Reference device supply current}}$$

The actual current can either be the one provided by a power supply or used by a device

**3.1.7****TP0 Character**

11 bit set including 8 data bits, 1 check bit (odd parity bit) and two synchronisation bits (start and stop bits)

**3.1.8****TP0 Distortion**

percentage ratio of the deviation time between the instant a transition occurs and the ideal transition instant, and the bit duration (~208 µs); the distortion is measured for each bit of a character, starting with the start bit

**3.1.9****TP0 Inter-Frame Time**

time between the end of a frame (end of stop bit for the last character) and the beginning of the next frame (beginning of the start bit of the first character)

**3.1.10****TP0 Line Load**

percentage ratio representing the proportion of actual character transmission during a specified integration time interval

**3.1.11****TP0 Odd parity bit**

check bit whose value is such that there is an odd number of logic "0" within the data and parity fields

**3.1.12****TP0 Repeater**

connects a primary segment to a secondary segment

**3.1.13****TP1 Backbone Couplers**

15 backbone couplers can be used to couple up to 16 zones to a full sized TP1 network

**3.1.14****TP1 Backbone Line**

the main line of the inner zone is called backbone line

**3.1.15****TP1 Bridge**

four TP1-64 physical segments can be combined to a line by using bridges. To such a line 256 devices can then be connected

**3.1.16****TP1 Line**

a TP1 line consists of a maximum of 256 devices, either directly connected in case of TP1-256 or separated over 4 physical segments in case of TP1-64, each with 64 devices

**3.1.17****TP1 Line Couplers**

routers that combine lines to a zone are called line couplers

**3.1.18****TP1 Logical Unit**

converts the serial bit stream to octets and octets to the serial bit stream, which is a serial stream of characters

# Bestelformulier

## Stuur naar:

NEN Standards Products & Services  
t.a.v. afdeling Klantenservice  
Antwoordnummer 10214  
2600 WB Delft



**NEN** Standards Products & Services

Postbus 5059  
2600 GB Delft

Vlinderweg 6  
2623 AX Delft

T (015) 2 690 390  
F (015) 2 690 271

[www.nen.nl/normshop](http://www.nen.nl/normshop)

## Ja, ik bestel

\_\_ ex. NEN-EN 50090-5-2:2004 en Gebouwbeheersystemen (HBES) - Deel € 99.00  
5-2: Media en media-afhankelijke lagen - Netwerk gebaseerd op HBES  
Klasse 1, Paarsgewijs gedraaid

**Wilt u deze norm in PDF-formaat? Deze bestelt u eenvoudig via**  
[www.nen.nl/normshop](http://www.nen.nl/normshop)

### Gratis e-mailnieuwsbrieven

Wilt u op de hoogte blijven van de laatste ontwikkelingen op het gebied van normen, normalisatie en regelgeving? Neem dan een gratis abonnement op een van onze e-mailnieuwsbrieven. [www.nen.nl/nieuwsbrieven](http://www.nen.nl/nieuwsbrieven)

## Gegevens

Bedrijf / Instelling \_\_\_\_\_

T.a.v. \_\_\_\_\_ O M O V

E-mail \_\_\_\_\_

Klantnummer NEN \_\_\_\_\_

Uw ordernummer \_\_\_\_\_ BTW nummer \_\_\_\_\_

Postbus / Adres \_\_\_\_\_

Postcode \_\_\_\_\_ Plaats \_\_\_\_\_

Telefoon \_\_\_\_\_ Fax \_\_\_\_\_

**Factuuradres** (indien dit afwijkt van bovenstaand adres)

Postbus / Adres \_\_\_\_\_

Postcode \_\_\_\_\_ Plaats \_\_\_\_\_

Datum \_\_\_\_\_ Handtekening \_\_\_\_\_

### Retourneren

Fax: 015 2 690 271

E-mail: [klantenservice@nen.nl](mailto:klantenservice@nen.nl)

Post: NEN Standards Products & Services,

t.a.v. afdeling Klantenservice  
Antwoordnummer 10214,  
2600 WB Delft

(geen postzegel nodig).

### Voorwaarden

- De prijzen zijn geldig tot 31 december 2018, tenzij anders aangegeven.
- Alle prijzen zijn excl. btw, verzend- en handelingskosten en onder voorbehoud bij o.m. ISO- en IEC-normen.
- Bestelt u via de normshop een pdf, dan betaalt u geen handeling en verzendkosten.
- Meer informatie: telefoon 015 2 690 391, dagelijks van 8.30 tot 17.00 uur.
- Wijzigingen en typfouten in teksten en prijsinformatie voorbehouden.
- U kunt onze algemene voorwaarden terugvinden op: [www.nen.nl/leveringsvoorwaarden](http://www.nen.nl/leveringsvoorwaarden).