
**Road vehicles — Component test
methods for electrical disturbances from
narrowband radiated electromagnetic
energy —**


**Part 2:
Absorber-lined shielded enclosure**

Véhicules routiers — Méthodes d'essai d'un équipement soumis à des perturbations électriques par rayonnement d'énergie électromagnétique en bande étroite —

Partie 2: Chambre anéchoïque

Dit document mag slechts op een stand-alone PC worden geïnstalleerd. Gebruik op een netwerk is alleen toestaan als een aanvullende licentieovereenkomst voor netwerkgebruik met NEN is afgesloten. This document may only be used on a stand-alone PC. Use in a network is only permitted when a supplementary license agreement for us in a network with NEN has been concluded.

Preview



Reference number
ISO 11452-2:2004(E)

© ISO 2004

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

Copyright
Preview

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Test conditions.....	1
5 Test location.....	2
6 Test apparatus and instrumentation.....	2
7 Test set-up.....	3
8 Test method.....	8
Annex A (informative) Artificial network (AN).....	10
Annex B (informative) Remote/local grounding.....	12
Annex C (informative) Function performance status classification (FPSC).....	14

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 11452-2 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 3, *Electrical and electronic equipment*.

This second edition cancels and replaces the first edition (ISO 11452-2:1995), which has been technically revised.

ISO 11452 consists of the following parts, under the general title *Road vehicles — Component test methods for electrical disturbances from narrowband radiated electromagnetic energy*:

- *Part 1: General principles and terminology*
- *Part 2: Absorber-lined shielded enclosure*
- *Part 3: Transverse electromagnetic mode (TEM) cell*
- *Part 4: Bulk current injection (BCI)*
- *Part 5: Stripline*
- *Part 7: Direct radio frequency (RF) power injection*

The radiating loop method is to form the subject of a future part 8.

Introduction

Immunity measurements of complete vehicles are generally able to be carried out only by the vehicle manufacturer, owing to, for example, high costs of an absorber-lined shielded enclosures, the desire to preserve the secrecy of prototypes or a large number of different vehicles models.

For research, development and quality control, a laboratory measuring method can be used by both vehicle manufacturers and equipment suppliers to test electronic components.

Copyright
Preview

Road vehicles — Component test methods for electrical disturbances from narrowband radiated electromagnetic energy —

Part 2: Absorber-lined shielded enclosure

1 Scope

This part of ISO 11452 specifies an absorber-lined shielded enclosure method for testing the immunity (off-vehicle radiation source) of electronic components for passenger cars and commercial vehicles regardless of the propulsion system (e.g. spark-ignition engine, diesel engine, electric motor). The device under test (DUT), together with the wiring (harness (prototype or standard test harness)), is subjected to an electromagnetic disturbance generated inside an absorber-lined shielded enclosure, with peripheral devices either inside or outside the enclosure. It is applicable only to disturbances from continuous narrowband electromagnetic fields. See ISO 11452-1 for general test conditions.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 11452-1, *Road vehicles — Component test methods for electrical disturbances from narrowband radiated electromagnetic energy — Part 1: General principles and terminology*¹⁾

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 11452-1 apply.

4 Test conditions

The applicable frequency range of the absorber-lined shielded enclosure test method is 80 MHz to 18 GHz.

The user shall specify the test severity level(s) over the frequency range. Suggested test levels are included in Annex C.

Standard test conditions shall be according to ISO 11452-1 for the following:

— test temperature;

1) To be published. (Revision of ISO 11452-1:2001)

- supply voltage;
- modulation;
- dwell time;
- frequency step sizes;
- definition of test severity levels;
- test signal quality.

5 Test location

The tests shall be performed in an absorber-lined shielded enclosure.

The purpose of such an enclosure is to create an isolated electromagnetic compatibility test facility which simulates open field testing. Basically, an absorber-lined shielded enclosure consists of a shielded room with absorbing material on its internal reflective surfaces, optionally excluding the floor. The design objective is to attenuate the reflected energy in the test area by at least 10 dB compared to the direct energy.

6 Test apparatus and instrumentation

6.1 General

Radiated electromagnetic fields are generated using antenna with a radio frequency (RF) energy source capable of producing the desired field strengths. A set of antennae and multiple RF amplifiers could be required to cover the range of test frequencies. The field is monitored electrically with small probes to ensure proper test levels. To reduce test error, the operation of the DUT is usually monitored by fibre-optic couplers.

6.2 Measuring equipment

6.2.1 Field-generating device: any available antenna (including high-power baluns, if appropriate) capable of radiating the specified field strength at the DUT with the available power may be used. The construction and orientation of any field-generating device shall be such that the generated field can be polarized in the mode specified in the test plan.

6.2.2 Field probes, which should be electrically small and isotropic. The transmission lines from the probes should be either fibre-optic links or very high resistance.

6.2.3 Artificial network(s) (AN): see 7.2 and Annex A.

6.2.4 HF generator, with internal (or external) modulation capabilities

6.2.5 High-power amplifier

6.2.6 Powermeter (or equivalent measuring instrument), for measuring forward power and reflected power.

6.3 Stimulation and monitoring of DUT

The device under test (DUT) shall be operated as required in the test plan by actuators that have a minimum effect on the electromagnetic characteristics, e.g. plastic blocks on the push-buttons, pneumatic actuators with plastic tubes.

Connections to equipment monitoring electromagnetic interference reactions of the DUT may be accomplished by using fibre-optics, or high-resistance leads. Other types of lead may be used but require extreme care to minimize interactions. The orientation, length and location of such leads shall be carefully documented to ensure repeatability of test results.

Any electrical connection of monitoring equipment to the DUT may cause malfunctions of the DUT. Extreme care shall be taken to avoid such an effect.

7 Test set-up

7.1 Ground plane

The ground plane shall be made of 0,5 mm thick (minimum) copper, brass or galvanized steel.

The minimum width of the ground plane shall be 1 000 mm. The minimum length of the ground plane shall be 2 000 mm, or the length of the entire underneath of the equipment plus 200 mm, whichever is the larger.

The height of the ground plane (test bench) shall be (900 ± 100) mm above the floor.

The ground plane shall be bonded to the shielded enclosure such that the d.c. resistance shall not exceed 2,5 m Ω . In addition, the bond straps shall be placed at a distance no greater than 0,3 m apart edge to edge.

7.2 Power supply and AN

Each DUT power supply lead shall be connected to the power supply through an AN.

Power supply is assumed to be negative ground. If the DUT utilizes a positive ground, then the test set-ups shown in the figures need to be adapted accordingly. Power shall be applied to the DUT via a 5 μ H/50 Ω AN (see Annex A for the schematic). The number of ANs required depends on the intended DUT installation in the vehicle.

- For a remotely grounded DUT (vehicle power return line longer than 200 mm), two ANs are required: one for the positive supply line and another for the power return line (see Annex B).
- For a locally grounded DUT (vehicle power return line 200 mm or shorter), only one AN is required, for the positive supply (see Annex B).

The AN(s) shall be mounted directly on the ground plane. The case or cases of the AN(s) shall be bonded to the ground plane.

The power supply return shall be connected to the ground plane between the power supply and the AN(s).

The measuring port of each AN shall be terminated with a 50 Ω load.

7.3 Location of DUT

The DUT shall be placed on a non-conductive, low relative permittivity (dielectric-constant) material ($\epsilon_r \leq 1,4$), at (50 ± 5) mm above the ground plane.

The case of the DUT shall not be grounded to the ground plane unless it is intended to simulate the actual vehicle configuration.

The face of the DUT shall be located at a distance of (200 ± 10) mm from the edge of the ground plane.

Bestelformulier

NEN

Stuur naar:

NEN Standards Products & Services
t.a.v. afdeling Klantenservice
Antwoordnummer 10214
2600 WB Delft

NEN Standards Products & Services

Postbus 5059
2600 GB Delft

Vlinderweg 6
2623 AX Delft

T (015) 2 690 390
F (015) 2 690 271

www.nen.nl/normshop

Ja, ik bestel

___ ex. ISO 11452-2:2004 en Wegvoertuigen - Elektrische storingen door elektromagnetische energie uitgestraald in een smalle band - Beproevingmethoden voor onderdelen - Deel 2: Met absorptiemateriaal beklede kamer € 73.12

Wilt u deze norm in PDF-formaat? Deze bestelt u eenvoudig via www.nen.nl/normshop

Gratis e-mailnieuwsbrieven

Wilt u op de hoogte blijven van de laatste ontwikkelingen op het gebied van normen, normalisatie en regelgeving? Neem dan een gratis abonnement op een van onze e-mailnieuwsbrieven. www.nen.nl/nieuwsbrieven

Retourneren

Fax: (015) 2 690 271
E-mail: klantenservice@nen.nl
Post: NEN Standards Products & Services,
t.a.v. afdeling Klantenservice
Antwoordnummer 10214,
2600 WB Delft
(geen postzegel nodig).

Gegevens

Bedrijf / Instelling _____

T.a.v. _____ O M O V

E-mail _____

Klantnummer NEN _____

Uw ordernummer _____

BTW nummer _____

Postbus / Adres _____

Postcode _____

Plaats _____

Telefoon _____

Fax _____

Factuuradres (indien dit afwijkt van bovenstaand adres)

Postbus / Adres _____

Postcode _____

Plaats _____

Datum _____

Handtekening _____

Voorwaarden

- De prijzen zijn geldig tot 31 december 2016, tenzij anders aangegeven.
- Alle prijzen zijn excl. btw, verzend- en handelingskosten en onder voorbehoud bij o.m. ISO- en IEC-normen.
- Bestelt u via de normshop een pdf, dan betaalt u geen handeling en verzendkosten.
- Meer informatie: telefoon (015) 2 690 391, dagelijks van 8.30 tot 17.00 uur.
- Wijzigingen en typfouten in teksten en prijsinformatie voorbehouden.
- U kunt onze algemene voorwaarden terugvinden op: www.nen.nl/leveringsvoorwaarden.