

praktijkrichtlijn

NPR-ISO/IEC TR 15938-8/A1 (en)

Information technology - Multimedia
content description interface - Part 8:
Extraction and use of MPEG-7
descriptions - Extensions of extraction
and use of MPEG-7 descriptions (ISO/IEC
TR 15938-8:2002/Amd 1:2004, IDT)

december 2004
ICS 35.040

Als Nederlands wijzigingsblad is aanvaard:

- ISO/IEC TR 15938-8:2002/Amd 1:2004, IDT

Normcommissie 381 029 "Multimedia/Hypermedia"

Apart from exceptions provided by the law, nothing from this publication may be duplicated and/or published by means of photocopy, microfilm, storage in computer files or otherwise, which also applies to full or partial processing, without the written consent of the Netherlands Standardization Institute.

The Netherlands Standardization Institute shall, with the exclusion of any other beneficiary, collect payments owed by third parties for duplication and/or act in and out of law, where this authority is not transferred or falls by right to the Reproduction Rights Foundation.

Auteursrecht voorbehouden. Behoudens uitzondering door de wet gesteld mag zonder schriftelijke toestemming van het Nederlands Normalisatie-instituut niets uit deze uitgave worden veelevoudigd en/of openbaar gemaakt door middel van fotokopie, microfilm, opslag in computerbestanden of anderszins, hetgeen ook van toepassing is op gehele of gedeeltelijke bewerking.

Het Nederlands Normalisatie-instituut is met uitsluiting van ieder ander gerechtigd de door derden verschuldigde vergoedingen voor veelevoudiging te innen en/of daartoe in en buiten rechte op te treden, voor zover deze bevoegdheid niet is overgedragen c.q. rechtens toekomt aan de Stichting Reprorecht.

Although the utmost care has been taken with this publication, errors and omissions cannot be entirely excluded. The Netherlands Standardization Institute and/or the members of the committees therefore accept no liability, not even for direct or indirect damage, occurring due to or in relation with the application of publications issued by the Netherlands Standardization Institute.

Hoewel bij deze uitgave de uiterste zorg is nagestreefd, kunnen fouten en onvolledigheden niet geheel worden uitgesloten. Het Nederlands Normalisatie-instituut en/of de leden van de commissies aanvaardden derhalve geen enkele aansprakelijkheid, ook niet voor directe of indirecte schade, ontstaan door of verband houdend met toepassing van door het Nederlands Normalisatie-instituut gepubliceerde uitgaven.

Voorbeeld
Preview

TECHNICAL
REPORT

ISO/IEC
TR
15938-8

First edition
2002-12-15

AMENDMENT 1
2004-11-15

**Information technology — Multimedia
content description interface —**

Part 8:
**Extraction and use of MPEG-7
descriptions**

**AMENDMENT 1: Extensions of extraction
and use of MPEG-7 descriptions**

*Technologies de l'information — Interface de description du contenu
multimédia —*

Partie 8: Extraction et utilisation des descriptions MPEG-7

*AMENDEMENT 1: Extensions d'extraction et utilisation des descriptions
MPEG-7*

Reference number

ISO/IEC TR 15938-8:2002/Amd.1:2004(E)



© ISO/IEC 2004

ISO/IEC TR 15938-8:2002/Amd.1:2004(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

Copyright
Preview

© ISO/IEC 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

In exceptional circumstances, the joint technical committee may propose the publication of a Technical Report of one of the following types:

- type 1, when the required support cannot be obtained for the publication of an International Standard, despite repeated efforts,
- type 2, when the subject is still under technical development or where for any other reason there is the future but not immediate possibility of an agreement on an International Standard;
- type 3, when the joint technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art", for example).

Technical Reports of types 1 and 2 are subject to review within three years of publication, to decide whether they can be transformed into International Standards. Technical Reports of type 3 do not necessarily have to be reviewed until the data they provide are considered to be no longer valid or useful.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO/IEC TR 15938-8:2002 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

NOTE This document preserves the sectioning of ISO/IEC TR 15938-8:2002. The text and figures given in this document are currently being considered as additions and/or modifications to those corresponding sections in ISO/IEC TR 15938-8:2002.

Information technology — Multimedia content description interface —

Part 8: Extraction and use of MPEG-7 descriptions

AMENDMENT 1: Extensions of extraction and use of MPEG-7 descriptions

Add after subclause 5.6:

5.7 GofGopFeature

This datatype is used to describe a certain visual feature representative of a series of video frames or collection of pictures. It is obtained by aggregating the visual descriptors extracted from each video frame or image in the collection.

5.7.1 Feature Extraction

First, the extraction algorithm computes a descriptor of the visual feature for each frame in the sequence or each image in the collection. The extraction is specified in the subclauses corresponding to the descriptor used (e.g. for HomogeneousTexture, subclause 4.3.1.1 is used). Once the values of the frame/image-based descriptors are computed, a instance of GofGopFeature is derived by the aggregation procedure corresponding to the descriptor used as defined in ISO/IEC 15938-3.

There are three aggregation methods (i.e. Average, Median, SplitMerge) as follows:

- Average:

Each component of descriptors in the GOF or GOP is summed and then averaged to compose the aggregated description

- Median:

Each component of descriptors in the GOF or GOP is sorted and then the middle value is selected to compose the aggregated description.

- SplitMerge:

The DominantColor descriptors from different images are aggregated by merging of the clusters ("Value" elements) of different descriptors based on their proximity in colour space (the clusters within the same descriptor are also included as a special case, although if the extraction algorithm from 4.2.3.1 is followed, their distance will be greater than DISTANCE_MIN specified below). The merging procedure is performed iteratively, starting with the closest pair and repeating until only a small number of combined clusters remains. The outline of this algorithm is as follows:

closest_distance=0

ISO/IEC TR 15938-8:2002/Amd.1:2004(E)

While (number_of_clusters > MAX_NUM_OF_CLUSTERS or

closest_distance < DISTANCE_MIN) {

1. find two closest clusters
2. merge these two clusters

}

The distance between clusters is defined as the Euclidean distance between cluster centres, DISTANCE_MIN is the same as in 4.2.3.1 and MAX_NUM_OF_CLUSTERS is equal to 8.

Merging of the clusters is performed as follows. The representative colour value for the merged cluster is a weighted average of the colour values of the component clusters, where the weights are the relative pixel counts in the clusters.

$$m = w_1 m_1 + w_2 m_2$$

Merging of the colour variances is based on the assumption that each colour component is independent and for each component we assume that we are calculating the variance of a weighted sum of two Gaussian distributions. This leads to the following formula for the variance of the merged cluster σ^2 :

$$\sigma^2 = w_1 \sigma_1^2 + w_2 \sigma_2^2 + w_1 w_2 (m_1 - m_2)^2,$$

where σ_1^2, σ_2^2 are the variances of the component clusters, m_1, m_2 are their means and w_1, w_2 are

$$w_1 = W1/(W1+W2), w_2 = W2/(W1+W2)$$

where W1 and W2 are the unweighted weights for sub-descriptors.

5.7.2 Similarity Matching Criteria

Matching of GofGopFeature is performed using the descriptors' matching function appropriate to the descriptor used. Only GofGopFeature descriptors characterizing the same feature can be compared. For example, GofGopFeature using the HomogeneousTexture descriptor for two different sequences can be compared. Some descriptors allow multiple aggregation methods, for example, the Color Layout or Edge Histogram descriptors. Matching of GofGopFeature describing the same feature but derived with a different aggregation method is possible.

5.7.3 DDL instantiation examples

In the following two examples, an instance of ColorLayout is embedded in the GofGopFeature datatype.

In the first example, there is no specification of aggregation method.

```
<GofGopFeature>
  <Descriptor xsi:type="mpeg7:ColorLayoutType">
    <YDCCoeff>48</YDCCoeff>
    <CbDCCoeff>34</CbDCCoeff>
    <CrDCCoeff>32</CrDCCoeff>
    <YACCCoeff5>12 10 13 9 10</YACCCoeff5>
    <CbACCCoeff2>14 15</CbACCCoeff2>
    <CrACCCoeff2>16 12</CrACCCoeff2>
  </Descriptor>
</GofGopFeature>
```


In the second example, "Average" is used to aggregate descriptions.

```
<GofGopFeature>
  <Descriptor xsi:type="mpeg7:ColorLayoutType" aggregation="Average">
    <YDCCoeff>48</YDCCoeff>
    <CbDCCoeff>34</CbDCCoeff>
    <CrDCCoeff>32</CrDCCoeff>
    <YACCoeff5>15 11 13 9 8</YACCoeff5>
    <CbACCoeff2>14 15</CbACCoeff2>
    <CrACCoeff2>16 12</CrACCoeff2>
  </Descriptor>
</GofGopFeature>
```

In the following example, an instance of DominantColor is embedded in the GofGopFeature datatype.

```
<GofGopFeature>
  <Descriptor xsi:type="mpeg7:DominantColorType" aggregation="SplitMerge">
    <SpatialCoherency>0</SpatialCoherency>
    <Value>
      <Percentage>5</Percentage>
      <Index>0 89 203</Index>
      <ColorVariance>0 1 1</ColorVariance>
    </Value>
    <Value>
      <Percentage>14</Percentage>
      <Index>120 43 74</Index>
      <ColorVariance>0 1 0</ColorVariance>
    </Value>
    <Value>
      <Percentage>2</Percentage>
      <Index>243 22 27</Index>
      <ColorVariance>0 0 0</ColorVariance>
    </Value>
  </Descriptor>
</GofGopFeature>
```

In the following two examples, an instance of EdgeHistogram is embedded in the GofGopFeature datatype.

In the first example, there is no specification of aggregation method

```
<GofGopFeature>
  <Descriptor xsi:type="mpeg7:EdgeHistogramType">
    <BinCounts>
      2 6 4 4 2 1 7 5 3 2 1 6 4 2 2 2 5 4
      5 3 1 5 5 6 5 2 6 5 4 4 1 6 4 4 4 0 6 3 5
      2 1 5 5 6 6 4 2 3 6 7 3 2 5 5 7 3 2 4 4 7
      1 5 6 4 6 1 5 7 4 5 1 6 4 6 5 1 3 4 7 6
    </BinCounts>
  </Descriptor>
</GofGopFeature>
```

In the second example, "Average" is used to aggregate descriptions.

ISO/IEC TR 15938-8:2002/Amd.1:2004(E)

```

<GofGopFeature>
  <Descriptor xsi:type="mpeg7:EdgeHistogramType" aggregation="Average">
    <BinCounts>
      2 6 4 4 2 1 7 5 3 2 1 6 4 2 2 2 5 4 5 3 1
      5 5 6 5 2 6 5 4 4 1 6 4 4 4 0 6 3 5 2 1 5
      5 6 6 4 2 3 6 7 3 2 5 5 7 3 2 4 4 7 1 5 6
      4 6 1 5 7 4 5 1 6 4 6 5 1 3 4 7 6
    </BinCounts>
  </Descriptor>
</GofGopFeature>

```

In the following two examples, an instance of HomogeneousTexture is embedded in the GofGopFeature datatype.

In the first example, there is no specification of aggregation method.

```

<GofGopFeature>
  <Descriptor xsi:type="mpeg7:HomogeneousTextureType">
    <Average>19</Average>
    <StandardDeviation>20</StandardDeviation>
    <Energy>
      103 87 99 130 97 73 112 109 122 132 108 102 105 113
      106 141 103 111 78 76 82 117 88 70 69 61 48 68 48
      53
    </Energy>
    <EnergyDeviation>
      106 84 94 130 94 75 107 104 117 128 100 99 97 107 92
      132 90 106 76 64 78 110 83 65 64 52 39 72 35 47
    </EnergyDeviation>
  </Descriptor>
</GofGopFeature>

```

In the second example, "Median" is used to aggregate descriptions.

```

<GofGopFeature>
  <Descriptor xsi:type="mpeg7:HomogeneousTextureType" aggregation = "Median" >
    <Average>19</Average>
    <StandardDeviation>20</StandardDeviation>
    <Energy>
      103 87 99 130 97 73 112 109 122 132 108 102 105 113
      106 141 103 111 78 76 82 117 88 70 69 61 48 68 48
      53
    </Energy>
    <EnergyDeviation>
      106 84 94 130 94 75 107 104 117 128 100 99 97 107 92
      132 90 106 76 64 78 110 83 65 64 52 39 72 35 47
    </EnergyDeviation>
  </Descriptor>
</GofGopFeature>

```

5.7.3 Conditions of Usage

There are no specific conditions and limitations on the use of this container datatype.

Add after subclause 6.8:

6.9 Color Temperature

The color temperature of an image specifies the color of illumination in the scene of the image. It is expressed by Kelvin (K) temperature scale in the [1667K, 25000K] range. Using this, the color temperature descriptor describes the perceptual temperature feeling of an image. It targets the perception-based image browsing that enables viewers to navigate and match images based on the temperature perception (i.e. hot, warm, moderate, and cool) of the image.

This descriptor is also useful when a user would like to change the illumination of scene (i.e. still images or video) in favor of the user's preference. For example, some people might want to see warmer images (e.g. taken under incandescent lights) than original images while some people might want to see cooler images (e.g. taken under bright daylights). Those effects can be automatically achieved by adjusting the color temperature.

6.9.1 Color Temperature Browsing

6.9.1.1 Feature Extraction

The (correlated) color temperature of the scene-illumination in the image is extracted as follows.

Note: In this section, several references are made to sRGB, perceived illuminant, and (correlated) color temperature and its reciprocal scale. All information on these subjects can be found in [AMD1-1][AMD1-2][AMD1-3][AMD1-4][AMD1-5].

6.9.1.1.1 The Overall View of Color Temperature Extraction Algorithm

- 1) Linearizing input image: $RGB \rightarrow R_l G_l B_l$
- 2) Converting $R_l G_l B_l$ into XYZ
- 3) Removing pixels that have the pixel value smaller than the low luminance threshold (T_{ll})
- 4) Averaging XYZ value for all remained pixels: $X_a Y_a Z_a$
- 5) Calculating the self-luminous threshold: $X_{T_s}, Y_{T_s}, Z_{T_s}$. If $X_{T_s}, Y_{T_s}, Z_{T_s}$ have the same values with the previous values, go to procedure 7), else remove pixels that have the pixel value bigger than the self-luminous threshold and repeat procedure 4) to 6)
- 6) Averaging XYZ value for all pixels remained, estimating it as the illuminant tri-stimulus values, and computing the scene-illuminant chromaticity coordinates (x_s, y_s) in CIE 1931 diagram
- 7) Converting the scene-illuminant chromaticity (x_s, y_s) into color temperature T_c
 - (1) Calculating the chromaticity coordinates (u_s, v_s) in CIE 1960 UCS diagram from (x_s, y_s)
 - (2) Finding two adjacent isothermure lines from (u_s, v_s) and obtaining the distance from those lines
 - (3) Computing the correlated color temperature using the distance ratio

6.9.1.1.2 The Detail of Extraction Algorithm

- 1) Linearizing input image: Obtain the linearized $R_l G_l B_l$ from the inverse gamma correction of the input RGB , which is the gamma-corrected for display devices

ISO/IEC TR 15938-8:2002/Amd.1:2004(E)

Note, it is assumed that an input image RGB is a gamma-corrected non-linear sR'G'B' in the range of 0~255(8bit) in the following equations.

if $R'_{sRGB}(i, j), G'_{sRGB}(i, j), B'_{sRGB}(i, j) \leq 0.03928 \times 255.0$,

$$R_{sRGB}(i, j) = \left(\frac{R'_{sRGB}(i, j)}{255} \right) \div 12.92$$

$$G_{sRGB}(i, j) = \left(\frac{G'_{sRGB}(i, j)}{255} \right) \div 12.92,$$

$$B_{sRGB}(i, j) = \left(\frac{B'_{sRGB}(i, j)}{255} \right) \div 12.92$$

else $R'_{sRGB}(i, j), G'_{sRGB}(i, j), B'_{sRGB}(i, j) > 0.03928 \times 255.0$,

$$R_l(i, j) = R_{sRGB}(i, j) = \left[\frac{\left(\frac{R'_{sRGB}(i, j)}{255} \right) + 0.055}{1.055} \right]^{2.4}$$

$$G_l(i, j) = G_{sRGB}(i, j) = \left[\frac{\left(\frac{G'_{sRGB}(i, j)}{255} \right) + 0.055}{1.055} \right]^{2.4}$$

$$B_l(i, j) = B_{sRGB}(i, j) = \left[\frac{\left(\frac{B'_{sRGB}(i, j)}{255} \right) + 0.055}{1.055} \right]^{2.4}$$

where (i, j) is the index for pixels

2) Converting linearized R_l, G_l, B_l into CIE 1931 tristimulus XYZ with conversion matrix M

$$\begin{bmatrix} X(i, j) \\ Y(i, j) \\ Z(i, j) \end{bmatrix} = M \cdot \begin{bmatrix} R_l(i, j) \\ G_l(i, j) \\ B_l(i, j) \end{bmatrix},$$

$$\text{where conversion matrix } M = \begin{bmatrix} 0.4124 & 0.3576 & 0.1805 \\ 0.2126 & 0.7152 & 0.0722 \\ 0.0193 & 0.1192 & 0.9505 \end{bmatrix}.$$

3) Removing pixels that have the pixel value smaller than the low luminance threshold(T_{ll})

$$\begin{cases} Y(i, j) < T_{ll}, & p(i, j) = 0 \\ \text{otherwise,} & p(i, j) = 255' \end{cases}$$

where $p(i, j)$ is the label for each pixel at the location (i, j) .

- 4) Averaging XYZ value for all pixels remained, which have $p(i, j) = 255$: $X_a Y_a Z_a$. $row * col$ intuitively means the number of all pixels remained.

$$X_a = \frac{1}{(row \times col)} \sum_{i=0}^{row-1} \sum_{j=0}^{col-1} X(i, j),$$

$$Y_a = \frac{1}{(row \times col)} \sum_{i=0}^{row-1} \sum_{j=0}^{col-1} Y(i, j),$$

$$Z_a = \frac{1}{(row \times col)} \sum_{i=0}^{row-1} \sum_{j=0}^{col-1} Z(i, j).$$

Calculating the self-luminous threshold: $X_{T_s}, Y_{T_s}, Z_{T_s}$

$$X_{T_s} = f \times k \times X_a,$$

$$Y_{T_s} = f \times k \times Y_a,$$

$$Z_{T_s} = f \times k \times Z_a.$$

where $f \times k \times X_a Y_a Z_a$ means the estimated illuminant level [AMD1-4].

- 6) If $X_{T_s}, Y_{T_s}, Z_{T_s}$ have the same values with the previous values, go to procedure 7), else remove pixels that have the pixel value bigger than the self-luminous threshold and repeat procedure 4) to 6)

If $(X_{T_s}(t) = X_{T_s}(t-1), Y_{T_s}(t) = Y_{T_s}(t-1), Z_{T_s}(t) = Z_{T_s}(t-1))$ { go to 7) }

else {

$$\begin{cases} X(i, j) > X_{T_s} \text{ or } Y(i, j) > Y_{T_s} \text{ or } Z(i, j) > Z_{T_s}, & p(i, j) = 0 \\ \text{otherwise,} & p(i, j) = 255 \end{cases}$$

}

repeat 4) ~ 6)

where t means the iteration time for the T_s and the initial values are set to

$$X_{T_s}(0) = 0, Y_{T_s}(0) = 0, Z_{T_s}(0) = 0.$$

- 7) Averaging the XYZ value for all pixels remained, estimating it as an illuminant tri-stimulus value, and computing the scene-illuminant chromaticity coordinates (x_s, y_s) in CIE 1931 diagram. Again, $row * col$ intuitively means the number of all pixels remained, which have $p(i, j) = 255$.

ISO/IEC TR 15938-8:2002/Amd.1:2004(E)

$$X_s = \frac{1}{(\text{row} \times \text{col})} \sum_{i=0}^{\text{row}-1} \sum_{j=0}^{\text{col}-1} X(i, j),$$

$$Y_s = \frac{1}{(\text{row} \times \text{col})} \sum_{i=0}^{\text{row}-1} \sum_{j=0}^{\text{col}-1} Y(i, j),$$

$$Z_s = \frac{1}{(\text{row} \times \text{col})} \sum_{i=0}^{\text{row}-1} \sum_{j=0}^{\text{col}-1} Z(i, j).$$

$$x_s = \frac{X_s}{X_s + Y_s + Z_s},$$

$$y_s = \frac{Y_s}{X_s + Y_s + Z_s}.$$

8) Converting the scene-illuminant chromaticity (x_s, y_s) into color temperature T_c .

(1) Calculating the chromaticity coordinates (u_s, v_s) in CIE 1960 UCS diagram from (x_s, y_s) .

$$u_s = \frac{4x_s}{-2x_s + 12y_s + 3},$$

$$v_s = \frac{6y_s}{-2x_s + 12y_s + 3}.$$

(2) Finding two adjacent isotherm lines [Mori et al (1968)] from (u_s, v_s) and obtaining the distance from those lines: if (u_s, v_s) is located between i -th and $i+1$ -th isotherm line then $d_i / d_{i+1} < 0$

$$d_i = \frac{(v_s - v_i) - t_i(u_s - u_i)}{(1 + t_i^2)^{1/2}},$$

where (u_i, v_i) , t_i : chromaticity coordinates and slope for representing the i -th isotherm line (Table AMD1-1 - Isotherm lines: Calculated in accordance with the method proposed by Mori et al.(1968): The color temperatures between 1667K and 25000K and corresponding parameters(u_i, v_i, t_i) are marked with blue fonts) and d_i : distance between (u_s, v_s) and the i th isotherm line.

(3) Calculating the correlated color temperature using the ratio of distance

$$T_c = \left[\frac{1}{T_i} + \frac{d_i}{d_i - d_{i+1}} \left(\frac{1}{T_{i+1}} - \frac{1}{T_i} \right) \right]^{-1},$$

where T_i is the color temperature for the cross point of the i -th isotherm line with the daylight locus. The color temperatures less than 1667K and larger than 25000K are tuned to 1667K and 25000K, respectively.

Table AMD1-1 — Isotemperature lines: Calculated in accordance with the method proposed by Mori et al.(1968)

i	Reciprocal Megakelvin	Temperature T (K)	u_i	v_i	t_i
1	0	Infinity	0.18006	0.26352	-0.24341
2	10	100,000	0.18066	0.26589	-0.25479
3	20	50,000	0.18133	0.26846	-0.26876
4	30	33,333	0.18208	0.27119	-0.28539
5	40	25,000	0.18293	0.27407	-0.30470
6	50	20,000	0.18388	0.27709	-0.32675
7	60	16,667	0.18494	0.28021	-0.35156
8	70	14,286	0.18611	0.28342	-0.37915
9	80	12,500	0.18740	0.28668	-0.40955
10	90	11,111	0.18880	0.28997	-0.44278
11	100	10,000	0.19032	0.29326	-0.47888
12	125	8,000	0.19462	0.30141	-0.58204
13	150	6,667	0.19962	0.30921	-0.70471
14	175	5,714	0.20525	0.31647	-0.84901
15	200	5,000	0.21142	0.32312	-1.0182
16	225	4,444	0.21807	0.32909	-1.2168
17	250	4,000	0.22511	0.33439	-1.4512
18	275	3,636	0.23247	0.33904	-1.7298
19	300	3,333	0.24010	0.34308	-2.0637
20	325	3,077	0.24702	0.34655	-2.4681
21	350	2,857	0.25591	0.34951	-2.9641
22	375	2,677	0.26490	0.35200	-3.5814
23	400	2,500	0.27218	0.35407	-4.3633
24	425	2,353	0.28039	0.35577	-5.3762
25	450	2,222	0.28863	0.35714	-6.7262
26	475	2,105	0.29685	0.35823	-8.5955
27	500	2,000	0.30505	0.35907	-11.324
28	525	1,905	0.31320	0.35968	-15.628
29	550	1,818	0.32129	0.36011	-23.325
30	575	1,739	0.32931	0.36038	-40.770
31	600	1,667	0.33724	0.36051	-116.45

Bestelformulier

NEN

Stuur naar:

NEN Standards Products & Services
t.a.v. afdeling Klantenservice
Antwoordnummer 10214
2600 WB Delft

NEN Standards Products & Services

Postbus 5059
2600 GB Delft
Vlinderweg 6
2623 AX Delft

T (015) 2 690 390
F (015) 2 690 271

www.nen.nl/normshop

Ja, ik bestel

__ ex. NPR-ISO/IEC TR 15938-8:2003/A1:2004 en Information technology - € 179.33
Multimedia content description interface - Part 8: Extraction and use of
MPEG-7 descriptions - Extensions of extraction and use of MPEG-7
descriptions

**Wilt u deze norm in PDF-formaat? Deze bestelt u eenvoudig via
www.nen.nl/normshop**

Gratis e-mailnieuwsbrieven

Wilt u op de hoogte blijven van de laatste ontwikkelingen op het gebied van normen,
normalisatie en regelgeving? Neem dan een gratis abonnement op een van onze
e-mailnieuwsbrieven. www.nen.nl/nieuwsbrieven

Retourneren

Fax: (015) 2 690 271
E-mail: klantenservice@nen.nl
Post: NEN Standards Products
& Services,
t.a.v. afdeling Klantenservice
Antwoordnummer 10214,
2600 WB Delft
(geen postzegel nodig).

Gegevens

Bedrijf / Instelling _____

T.a.v. _____ O M O V

E-mail _____

Klantnummer NEN _____

Uw ordernummer _____ BTW nummer _____

Postbus / Adres _____

Postcode _____ Plaats _____

Telefoon _____ Fax _____

Factuuradres (indien dit afwijkt van bovenstaand adres)

Postbus / Adres _____

Postcode _____ Plaats _____

Datum _____ Handtekening _____

Voorwaarden

- De prijzen zijn geldig tot 31 december 2016, tenzij anders aangegeven.
- Alle prijzen zijn excl. btw, verzend- en handelingskosten en onder voorbehoud bij o.m. ISO- en IEC-normen.
- Bestelt u via de normshop een pdf, dan betaalt u geen handeling en verzendkosten.
- Meer informatie: telefoon (015) 2 690 391, dagelijks van 8.30 tot 17.00 uur.
- Wijzigingen en typfouten in teksten en prijsinformatie voorbehouden.
- U kunt onze algemene voorwaarden terugvinden op: www.nen.nl/leveringsvoorwaarden.